

# {10.80}



## Super Erecta Pro®

### Durable and Cleanable. The original — reinnovated.

Corrosion resistant shelving constructed of removable polymer open grid shelf mats over a wire shelf frame. Shelf frames and posts have Metroseal epoxy coating over an electroplated substrate. Shelves with polymer mats offer a 20 year limited warranty against corrosion, while posts offer a 15 year warranty against corrosion. Microban® antimicrobial product protection is built into the frames, shelf mats and posts to help keep product cleaner between cleanings. Shelf has a rigid four-sided frame with center truss(es). Robust corner provides complete 360° capture of the split sleeves and post for added stability. Stationary units have maximum capacity of 2,000 lbs. (907kg) evenly distributed. Mobile units (with stem casters) offer a maximum total unit load of 900 lbs. (408kg). Units assemble easily — shelves mount on split sleeves along grooved, numbered posts and adjust on 1" (25mm) increments.

- **Prolonged durability:** Polymer shelf mats are corrosion proof and impact resistant. They will not chip, rust, or corrode.
- **Easy to clean:** Removable polymer shelf mats can easily be lifted off the shelf frames for cleaning in sinks or wash/dish machines.
- **Strong and robust:** Steel corners, side and center supports assure a sturdy and stable weight bearing surface.  
Weight capacities for evenly distributed loads:  
800 lbs. (363kg) per shelf for lengths of 24" to 48" (610 to 1220mm)  
600 lbs. (275kg) per shelf for lengths of 54" (1370mm) or longer  
2,000 lbs. (907kg) maximum per stationary unit.
- **Interchangeable:** Super Erecta Pro shelves are compatible on the same shelving units with other Super Erecta shelving options: Super Erecta wire, Super Adjustable Super Erecta, Solid Super Erecta shelves, Dunnage shelves, Cantilever shelves. Super Erecta Pro shelves can be used with Post-Type Wall Mounts, Direct Wall Mounts, SmartWall Wall Mounts, Security Units, Top Track, and qwikTRAK systems.
- **Microban® Product Protection:** Microban® antimicrobial product protection is built into the shelf mats and the Metroseal Green epoxy coating protects the product from bacteria that cause odors and product degradation. Microban protection keeps the product "cleaner between cleanings".
- **Efficient use of storage space:** Shelves can be adjusted at 1" (25mm) increments along the post to maximize the use of available vertical storage space.
- **Open Grid Shelf Mats:** Open grid shelves promote air circulation and light penetration.
- **Fast, Easy Assembly:** Super Erecta Pro units assemble easily in minutes, without tools. SiteSelect posts have numbered grooves and feature unique double grooves every 8" (203mm) to help position the shelves.
- **Warranty against rust and corrosion:** Shelves with polymer shelf mats – 20 years. Posts – 15 years. Shelf mats are constructed of polypropylene and will never rust.



For stem casters,  
see catalog sheet #11.20



MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban® Products Company, Huntersville, NC. Microban® product protection does not by itself protect a user from food borne illness. Product must be routinely cleaned.

Supports good  
**HACCP**  
processes




All Metro Catalog Sheets are available on our website: [metro.com](https://metro.com)

# Super Erecta Pro®

## Standard Shelves

- Part number includes shelf with removable polymer shelf mats and one bag of split sleeves

| Nominal Width/Length (in.) (mm) | Approx. Pkd. Wt. (lbs.) (kg) | Model No. SE Pro Metroseal Green |
|---------------------------------|------------------------------|----------------------------------|
| 14x24 355x610                   | 4.5 2.0                      | PR1424NK3                        |
| 14x30 355x760                   | 6.3 2.9                      | PR1430NK3                        |
| 14x36 355x914                   | 8.0 3.6                      | PR1436NK3                        |
| 14x42 355x1060                  | 10.0 4.5                     | PR1442NK3                        |
| 14x48 355x1219                  | 11.9 5.4                     | PR1448NK3                        |
| 14x60 355x1524                  | 14.9 6.8                     | PR1460NK3                        |
| 14x72 355x1829                  | 18.3 8.3                     | PR1472NK3                        |
| 18x24 457x610                   | 6.0 2.7                      | PR1824NK3                        |
| 18x30 457x760                   | 7.8 3.5                      | PR1830NK3                        |
| 18x36 457x914                   | 9.5 4.2                      | PR1836NK3                        |
| 18x42 457x1060                  | 11.3 5.0                     | PR1842NK3                        |
| 18x48 457x1219                  | 13.0 5.8                     | PR1848NK3                        |
| 18x54 457x1372                  | 14.8 6.6                     | PR1854NK3                        |
| 18x60 457x1524                  | 16.5 7.4                     | PR1860NK3                        |
| 18x72 457x1829                  | 19.8 8.8                     | PR1872NK3                        |
| 21x24 530x610                   | 8.0 3.6                      | PR2124NK3                        |
| 21x30 530x760                   | 9.5 4.2                      | PR2130NK3                        |
| 21x36 530x914                   | 11.3 5.0                     | PR2136NK3                        |
| 21x42 530x1060                  | 12.5 5.6                     | PR2142NK3                        |
| 21x48 530x1219                  | 14.3 6.4                     | PR2148NK3                        |
| 21x54 530x1372                  | 16.5 7.4                     | PR2154NK3                        |
| 21x60 530x1524                  | 18.3 8.1                     | PR2160NK3                        |
| 21x72 530x1829                  | 21.5 9.6                     | PR2172NK3                        |
| 24x24 610x610                   | 9.5 4.2                      | PR2424NK3                        |
| 24x30 610x760                   | 11.3 5.0                     | PR2430NK3                        |
| 24x36 610x914                   | 13.0 5.8                     | PR2436NK3                        |
| 24x42 610x1060                  | 14.0 6.3                     | PR2442NK3                        |
| 24x48 610x1219                  | 15.5 6.9                     | PR2448NK3                        |
| 24x54 610x1372                  | 18.3 8.1                     | PR2454NK3                        |
| 24x60 610x1524                  | 20.0 8.9                     | PR2460NK3                        |
| 24x72 610x1829                  | 23.3 10.4                    | PR2472NK3                        |



**Actual Dimensions:** Width: Add 1/4" (6mm) to nominal size. Length: Subtract 1/4" (6mm) from nominal size.

**Note:** Polymer Shelf mats are designed to fit Super Erecta Pro shelves and cannot be retrofitted to Super Erecta wire shelves.

## Replacement Split Sleeves

**Model No. 9985** (Bag of four sets.)

## Specifications

- Shelf frames:** Carbon steel with Metroseal Green epoxy coating.
- Polymer Shelf mats:** polypropylene.
- Microban® antimicrobial product protection** is built into the polymer shelf mats and Metroseal Green epoxy coating.
- NSF listed for all environments.**
- Continuous Temperature:** Super Erecta Pro Shelves can be used continuously within a range of -20/120° F (-29/49° C). For cleaning only, the unloaded product or shelf mats may be intermittently exposed to temperatures up to 200° F (93° C).

**NOTE:** Not suitable for cart wash applications.

## SHELVING HEIGHT GUIDELINES

| Shelf Depth                   | 14" (356mm)  | 18" (457mm)  | 21" (533mm)  | 24" (610mm)  |
|-------------------------------|--------------|--------------|--------------|--------------|
| Maximum Post Height Allowable | 63" (1600mm) | 86" (2184mm) | 86" (2184mm) | 96" (2438mm) |
| Stationary                    | 63" (1600mm) | 86" (2184mm) | 86" (2184mm) | 96" (2438mm) |
| Mobile                        | 54" (1372mm) | 74" (1880mm) | 74" (1880mm) | 86" (2184mm) |

Note: For stationary units with foot plates or wall brackets properly attached to the floor or wall, the maximum allowable height is 96" (2438mm).

## SiteSelect Posts

Stationary post height includes leveling bolt.

## STATIONARY

| Actual Height (in.) (mm) | Approx. Pkd. Wt. (lbs.) (kg) | Model No. Metroseal Green | Model No. Stainless |
|--------------------------|------------------------------|---------------------------|---------------------|
| 14 1/2 370               | 1.0 0.5                      | 13PK3                     | 13PS                |
| 34 1/2 875               | 2.0 0.9                      | 33PK3                     | 33PS                |
| 54 9/16 1385             | 3.0 1.4                      | 54PK3                     | 54PS                |
| 62 9/16 1590             | 3.5 1.6                      | 63PK3                     | 63PS                |
| 74 5/8 1895              | 4.0 1.8                      | 74PK3                     | 74PS                |
| 86 5/8 2200              | 5.0 2.3                      | 86PK3                     | 86PS                |

## MOBILE (For use with stem casters)

| Actual Height (in.) (mm) | Approx. Pkd. Wt. (lbs.) (kg) | Model No. Metroseal Green | Model No. Stainless |
|--------------------------|------------------------------|---------------------------|---------------------|
| 13 3/4 349               | 1.0 0.5                      | 13UPK3                    | 13UPS               |
| 33 3/4 857               | 2.0 0.9                      | 33UPK3                    | 33UPS               |
| 53 13/16 1366            | 3.0 1.4                      | 54UPK3                    | 54UPS               |
| 61 13/16 1570            | 3.5 1.6                      | 63UPK3                    | 63UPS               |
| 69 3/4 1772              | 3.8 1.7                      | 70UPK3                    | —                   |
| 73 7/8 1876              | 4.0 1.8                      | 74UPK3                    | 74UPS               |
| 85 7/8 2181              | 5.0 2.3                      | 86UPK3                    | 86UPS               |

**NOTE:** Special length posts are available. Consult your Metro representative.

**"S" Hook:** Used to "add on" one or multiple Super Erecta Pro shelving units while eliminating the cost of two posts per unit. Can be used to join units end-to-end, back-to-back, at right angles, etc. Two "S" hooks are required for each shelf.

## Model No. Q9995Z

### Notes about "add-on" units.

- Add-on (Adjacent) units must be configured entirely of one style of shelf. (Example: Adjacent unit may be configured entirely of Super Erecta Pro OR entirely of Super Erecta Wire/Super Adjustable shelves.)
- To connect an adjacent Super Erecta or Super Adjustable Super Erecta wire shelving unit to a Super Erecta Pro unit using S-hooks, the adjacent unit must use S-hook model number Q9995Z.
- A mixed shelving unit having a combination of Super Erecta Pro, Super Erecta wire, and Super Adjustable cannot be connected to another unit with "S" Hooks.

