{10.80}



# Super Erecta Pro®

## Durable and Cleanable. The original — reinnovated.

Corrosion resistant shelving constructed of removable polymer open grid shelf mats over a wire shelf frame. Shelf frames and posts have Metroseal epoxy coating over an electroplated substrate. Shelves with polymer mats offer a 20 year limited warranty against corrosion, while posts offer a 15 year warranty against corrosion. Microban® antimicrobial product protection is built into the frames, shelf mats and posts to help keep product cleaner between cleanings. Shelf has a rigid four-sided frame with center truss(es). Robust corner provides complete 360° capture of the split sleeves and post for added stability. Stationary units have maximum capacity of 2,000 lbs. (907kg) evenly distributed. Mobile units (with stem casters) offer a maximum total unit load of 900 lbs. (408kg). Units assemble easily — shelves mount on split sleeves along grooved, numbered posts and adjust on 1" (25mm) increments.

- Prolonged durability: Polymer shelf mats are corrosion proof and impact resistant.
   They will not chip, rust, or corrode.
- Easy to clean: Removable polymer shelf mats can easily be lifted off the shelf frames for cleaning in sinks or wash/dish machines.
- Strong and robust: Steel corners, side and center supports assure a sturdy and stable weight bearing surface.
  Weight capacities for evenly distributed loads:
  800 lbs. (363kg) per shelf for lengths of 24" to 48" (610 to 1220mm) 600 lbs. (275kg) per shelf for lengths of 54" (1370mm) or longer 2,000 lbs. (907kg) maximum per stationary unit.
- Interchangeable: Super Erecta Pro shelves are compatible on the same shelving units with other Super Erecta shelving options: Super Erecta wire, Super Adjustable Super Erecta, Solid Super Erecta shelves, Dunnage shelves, Cantilever shelves. Super Erecta Pro shelves can be used with Post-Type Wall Mounts, Direct Wall Mounts, SmartWall Wall Mounts, Security Units, Top Track, and qwikTRAK systems.
- Microban® Product Protection: Microban® antimicrobial product protection is built
  into the shelf mats and the Metroseal Green epoxy coating protects the product from
  bacteria that cause odors and product degradation. Microban protection keeps the
  product "cleaner between cleanings".
- Efficient use of storage space: Shelves can be adjusted at 1" (25mm) increments along the post to maximize the use of available vertical storage space.
- Open Grid Shelf Mats: Open grid shelves promote air circulation and light penetration.
- Fast, Easy Assembly: Super Erecta Pro units assemble easily in minutes, without tools.
   SiteSelect posts have numbered grooves and feature unique double grooves every
   8" (203mm) to help position the shelves.
- Warranty against rust and corrosion: Shelves with polymer shelf mats 20 years.
   Posts 15 years. Shelf mats are constructed of polypropylene and will never rust.









MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban® Products Company, Huntersville, NC. Microban® product protection does not by itself protect a user from food borne illness. Product must be routinely cleaned.





All Metro Catalog Sheets are available on our website: metro.com

Outside U.S. and Canada: metro.com/contactus




# Super Erecta Pro®

#### **Standard Shelves**

 Part number includes shelf with removable polymer shelf mats and one bag of split sleeves

	ominal th/Length (mm)	Approx Pkd. Wt. (lbs.) (kg)		Model No. SE Pro Metroseal Green
14x24	355x610	4.5	2.0	PR1424NK3
14x30	355x760	6.3	2.9	PR1430NK3
14x36	355x914	8.0	3.6	PR1436NK3
14x42	355x1060	10.0	4.5	PR1442NK3
14x48	355x1219	11.9	5.4	PR1448NK3
14x60	355x1524	14.9	6.8	PR1460NK3
14x72	355x1829	18.3	8.3	PR1472NK3
18x24	457x610	6.0	2.7	PR1824NK3
18x30	457x760	7.8	3.5	PR1830NK3
18x36	457x914	9.5	4.2	PR1836NK3
18x42	457x1060	11.3	5.0	PR1842NK3
18x48	457x1219	13.0	5.8	PR1848NK3
18x54	457x1372	14.8	6.6	PR1854NK3
18x60	457x1524	16.5	7.4	PR1860NK3
18x72	457x1829	19.8	8.8	PR1872NK3
21x24	530x610	8.0	3.6	PR2124NK3
21x30	530x760	9.5	4.2	PR2130NK3
21x36	530x914	11.3	5.0	PR2136NK3
21x42	530x1060	12.5	5.6	PR2142NK3
21x48	530x1219	14.3	6.4	PR2148NK3
21x54	530x1372	16.5	7.4	PR2154NK3
21x60	530x1524	18.3	8.1	PR2160NK3
21x72	530x1829	21.5	9.6	PR2172NK3
24x24	610x610	9.5	4.2	PR2424NK3
24x30	610x760	11.3	5.0	PR2430NK3
24x36	610x914	13.0	5.8	PR2436NK3
24x42	610x1060	14.0	6.3	PR2442NK3
24x48	610x1219	15.5	6.9	PR2448NK3
24x54	610x1372	18.3	8.1	PR2454NK3
24x60	610x1524	20.0	8.9	PR2460NK3
24x72	610x1829	23.3	10.4	PR2472NK3



**Actual Dimensions:** Width: Add 1/4" (6mm) to nominal size. Length: Subtract 1/4" (6mm) from nominal size.

**Note:** Polymer Shelf mats are designed to fit Super Erecta Pro shelves and cannot be retrofitted to Super Erecta wire shelves.

Replacement Split Sleeves Model No. 9985 (Bag of four sets.)

### **Specifications**

- Shelf frames: Carbon steel with Metroseal Green epoxy coating.
- Polymer Shelf mats: polypropylene.
- Microban® antimicrobial product protection is built into the polymer shelf mats and Metroseal Green epoxy coating.
- NSF listed for all environments.
- Continuous Temperature: Super Erecta Pro Shelves can be used continuously within a range of -20/120° F (-29/49° C). For cleaning only, the unloaded product or shelf mats may be intermittently exposed to temperatures up to 200° F (93° C).

NOTE: Not suitable for cart wash applications.

#### SHELVING HEIGHT GUIDELINES

Shelf Depth	14" (356mm)	18" (457mm)	21" (533mm)	24" (610mm)
Maxium Post Height Allowable				
Stationary	63" (1600mm)	86" (2184mm)	86" (2184mm)	96" (2438mm)
Mobile	54" (1372mm)	74" (1880mm)	74" (1880mm)	86" (2184mm)

Note: For stationary units with foot plates or wall brackets properly attached to the floor or wall, the maximum allowable height is 96" (2438mm).

#### SiteSelect Posts

Stationary post height includes leveling bolt.

Actual Height (in.) (mm)	<b>MOBILE</b> (For use with stem casters)								ONARY	STATIC		
(in.)         (mm)         (lbs.)         (kg)         Green         Stainless         (in.)         (mm)         (lbs.)         (kg)         Green           14½         370         1.0         0.5         13PK3         13PS         13³¼         349         1.0         0.5         13UPK3           34½         875         2.0         0.9         33PK3         33PS         33³¼         857         2.0         0.9         33UPK3           549¼         1385         3.0         1.4         54PK3         54PS         53¹³⅓         1366         3.0         1.4         54UPK3           62⁰⅓         1590         3.5         1.6         63PK3         63PS         61¹³⅓         1570         3.5         1.6         63UPK3           -         -         -         -         -         69³¼         1772         3.8         1.7         70UPK3	•	Model No.	rox.	` Approx.			Model No.	Approx.	App			
14½       370       1.0       0.5       13PK3       13PS       13³¼       349       1.0       0.5       13UPK3         34½       875       2.0       0.9       33PK3       33PS       33³¼       857       2.0       0.9       33UPK3         54³⅓16       1385       3.0       1.4       54PK3       54PS       53¹³⅓16       1366       3.0       1.4       54UPK3         62³√16       1590       3.5       1.6       63PK3       63PS       61¹³√16       1570       3.5       1.6       63UPK3         -       -       -       -       -       69³¼       1772       3.8       1.7       70UPK3	Model No.	Metroseal	Wt.	odel No. Actual Height Pkd. Wt.		Model No.	Metroseal	kd. Wt.	Pkd	Height	Actual	
34½       875       2.0       0.9       33PK3       33PS       33¾       857       2.0       0.9       33UPK3         54¾16       1385       3.0       1.4       54PK3       54PS       53⅓16       1366       3.0       1.4       54UPK3         62¾16       1590       3.5       1.6       63PK3       63PS       61⅓16       1570       3.5       1.6       63UPK3         -       -       -       -       69¾4       1772       3.8       1.7       70UPK3	Stainless	Green	(kg)	(lbs.)	(mm)	(in.)	Stainless	Green	s.) (kg)	(lbs.)	(mm)	(in.)
549/16 1385       3.0 1.4       54PK3       54PS       5313/16 1366       3.0 1.4       54UPK3         629/16 1590       3.5 1.6       63PK3       63PS       6113/16 1570       3.5 1.6       63UPK3         — — — — — — — 693/4 1772       3.8 1.7       70UPK3	13UPS	13UPK3	0.5	1.0	349	13 <sup>3</sup> / <sub>4</sub>	13PS	13PK3	0 0.5	1.0	370	14 <sup>1</sup> / <sub>2</sub>
62 <sup>9</sup> / <sub>16</sub> 1590 3.5 1.6 <b>63PK3 63PS</b> 61 <sup>13</sup> / <sub>16</sub> 1570 3.5 1.6 <b>63UPK3</b> — — — — — — 69 <sup>3</sup> / <sub>4</sub> 1772 3.8 1.7 <b>70UPK3</b>	<b>33UPS</b>	33UPK3	0.9	2.0	857	333/4	33PS	33PK3	0.9	2.0	875	341/2
69 <sup>3</sup> / <sub>4</sub> 1772 3.8 1.7 <b>70UPK3</b>	54UPS	54UPK3	1.4	3.0	1366	5313/16	54PS	54PK3	0 1.4	3.0	1385	549/16
	63UPS	63UPK3	1.6	3.5	1570	6113/16	63PS	63PK3	5 1.6	3.5	1590	629/16
7451 4005 40 40 74010 7400 7071 4070 40 40 741010	_	70UPK3	1.7	3.8	1772	693/4	_	_	- —	_	_	_
74% 1895 4.0 1.8 <b>74PK3 74PS</b> 73% 1876 4.0 1.8 <b>740PK3</b>	<b>74UPS</b>	<b>74UPK3</b>	1.8	4.0	1876	$73^{7}/8$	74PS	74PK3	0 1.8	4.0	1895	745/8
86 <sup>5</sup> / <sub>8</sub> 2200 5.0 2.3 <b>86PK3 86PS</b> 85 <sup>7</sup> / <sub>8</sub> 2181 5.0 2.3 <b>86UPK3</b>	86UPS	86UPK3	2.3	5.0	2181	85 <sup>7</sup> /8	86PS	86PK3	0 2.3	5.0	2200	86 <sup>5</sup> /8

NOTE: Special length posts are available. Consult your Metro representative.

"S" Hook: Used to "add on" one or multiple Super Erecta Pro shelving units while eliminating the cost of two posts per unit. Can be used to join units end-to-end, back-to-back, at right angles, etc. Two "S" hooks are required for each shelf.

## Model No. Q9995Z

### Notes about "add-on" units.

- Add-on (Adjacent) units <u>must</u> be configured entirely of one style of shelf. (Example: Adjacent unit may be configured entirely of Super Erecta Pro OR entirely of Super Erecta Wire/Super Adjustable shelves.)
- To connect an adjacent Super Erecta or Super Adjustable Super Erecta wire shelving unit to a Super Erecta Pro unit using S-hooks, the adjacent unit must use S-hook model number Q9995Z.
- A mixed shelving unit having a combination of Super Erecta Pro, Super Erecta wire, and Super Adjustable <u>cannot</u> be connected to another unit with "S" Hooks.



