ICB TWIN TF 1.5 Gal PE, 120/240V SST

Height: 34.0" Width: 22.6" Depth: 23.3" (86.4cm) (57.4cm) (59.2cm)





- Intuitive 4.3" touchscreen with user interface provides an enhanced experience when operating and programming the brewers
- SmartWAVE sprayhead technology creates an industry best uniformity of extraction for exceptionally smooth tasting coffee
- Platinum Edition SmartWave technology delivers a timed air purge at the end of the brew cycle, removing residual water from the sprayhead, reducing lime build up and ultimately extending the life of the equipment
- The ICB Twin Infusion Series coffee brewer delivers twice the brew capacity, from a single platform
- Multiple recipes from one footprint --- with six brew buttons and three batch sizes
- Large 5.6 gallon (21.2L) tank provides back-to-back brewing capacity
- USB port for easy programming
- Digital readout displays in English, Spanish, or French ---for easier programming and control
- Energy-saver mode reduces tank temperature during idle periods
- Electronic funnel lock prevents removal of each brew funnel until drip- through is complete
- ICB TF 54200.0101 is compatible with new TF 1.5-gallon ThermoFresh® Servers (with Base), all previous generations of TF 1.5-gallon TF Servers (with Base), Titan® 1.5-gallon servers, and Airpots
- Optional BUNNlink® remote monitoring support (kit required)
 Agency:





Specifications

Product #: 54200.0101 Funnel: Smart Funnel

Water Access: Plumbed Faucet: Lower

Interface: Wireless Legs: 4" Satin Nickel Legs

Finish: Stainless

Additional Features

Hot Water Button

Electrical & Capacity

120/240	25	6000	Yes/	-	280	60°F (15.5°C)	1	3	60	
Volts*	Amps	Watts	Cord Attached	Plug Type	8oz cups/hr 236ml cups/hr	Input H ² O Temp.	Phase	# Wires plus Ground	Hertz	

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

Plumbing Requirements


	Tranibing Requirements							
PSI kPa		kPa	Fitting Supplied	Water Flow Required (GPM)				
	20-90 138-621		3/8" Male Flare Fitting	1.00				


CAD Drawings


2D	Revit	KLC					
•	•	•					

WARNING: This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov









Unit				Shipping				
	Height	Width	Depth	Height	Width	Depth	Weight	Volume
English	34.0 in.	22.6 in.	23.3 in.	30.8 in.	25.8 in.	26.7 in.	87.600 lbs	12.259 ft ³
Metric	86.4 cm	57.4 cm	59.2 cm	78.1 cm	65.6 cm	67.8 cm	39.735 kgs	0.347 m³



Related Products & Accessories: ICB TWIN TF 1.5 Gal PE, 120/240V SST(54200.0101)



FILTERS, GOURMET 500 500/1 50/CL

Product #: 20138.1000



NON-LOCKING STAND ASSY, TF SERVER GEN3

Product #: 39795.0200



STAND ASSY KIT, TF SERVER

Product #: 54473.1000

FUNNEL ASSY, SST INFUSION COFFEE

Product #: 54675.0001



Serving & Holding Options: ICB TWIN TF 1.5 Gal PE, 120/240V SST(54200.0101)



TF SERVER, 1G DSG GEN3

Product #:42700.0200



TF SERVER, 1G DSG GEN3 NOBASE

Product #:42700.0250



TF SERVER, 1.5G DSG GEN3

Product #:42750.0200



TF SERVER, 1.5G DSG GEN3 NOBASE

Product #:42750.0250



TF SERVER, 1G MECH GEN3

Product #:44000.0200



TF SERVER, 1G MECH GEN3 NOBASE

Product #:44000.0250



TF SERVER, 1.5G MECH GEN3

Product #:44050.0200



TF SERVER, 1.5G MECH NOBASE GEN3

Product #:44050.0250

