

Enterprise® SCALES



LEGAL-FOR-TRADE ACCURACY

DETECTO APS70 with
optional APSPOST tower,
APSRD remote display,
BT1214 balltop transfer,
and APSWIFI wireless Ethernet



**4 Platform Sizes
6 Capacities**

DETECTO®

DETECTO's Enterprise® APS series logistics scales are designed to interface fluidly with UPS WorldShip® and virtually any shipping and manifesting software. The Enterprise® is an ideal choice for mail rooms, shipping departments, parcel and shipping stores, and retail counters. Capacities are available up to 250 pounds with 18 x 18 inch brushed stainless steel platforms. The scale includes an RS-232 serial cable and AC adapter, plus optional Wi-Fi is available for network connectivity. Optional ball top transfers ease conveyor line integration.



APS8
APS10
APS12

APS160
APS15
APS20
APS30
APS70
APS150

APS250

OPTIONAL ACCESSORIES



Model APSWIFI
(60 ft. range)

Remote Display

Additional LCD display, 6 ft. cable,
wall mounting bracket, and Velcro strip
Model APSRD



Tower Post

Remote display post
(14-in / 35.5-cm high)
Model APSPOST

Ball Top Transfers

Available for 12 x 14 and
18 x 18 inch platforms
Model BT1214 / BT1818



REMOTE DISPLAY MOUNTING VARIATIONS

**Mount APSRD
on wall with included
Velcro strips**



**Mount APSRD
on wall with mount-
ing bracket and
screws**



**Mount APSRD
on APSPOST
display tower**



MODEL	PLATFORM SIZE	CAPACITY	INCREMENTS	DIVISIONS	LOAD CELL	SHIP WT.	UPC CODE
APS8	6 in x 10 in / 15 cm x 25 cm	15 lb	0.01 lb	1,500	TSP-10KG	10 lb / 4.5 kg	809161193107
		7.5 kg	0.005 kg	1,500			
APS10	6 in x 10 in / 15 cm x 25 cm	30 lb	0.01 lb	3,000	TSP-15KG	10 lb / 4.5 kg	809161191202
		15 kg	0.005 kg	3,000			
APS12	6 in x 10 in / 15 cm x 25 cm	160 oz	0.1 oz	1,600	TSP-10KG	10 lb / 4.5 kg	809161193206
APS160	10 in x 10 in / 25 cm x 25 cm	160 oz	0.1 oz	1,600	TSP-10KG	12 lb / 5.4 kg	809161191301
APS15	10 in x 10 in / 25 cm x 25 cm	15 lb	0.01 lb	1,500	TSP-10KG	12 lb / 5.4 kg	809161191400
		7.5 kg	0.005 kg	1,500			
APS20	10 in x 10 in / 25 cm x 25 cm	30 lb	0.01 lb	3,000	TSP-15KG	12 lb / 5.4 kg	809161193305
		15 kg	0.005 kg	3,000			
APS30	12 in x 14 in / 31 cm x 36 cm	30 lb	0.01 lb	1,500	TSP-15KG	15.4 lb / 7 kg	809161191509
		15 kg	0.005 kg	3,000			
APS70	12 in x 14 in / 31 cm x 36 cm	70 lb	0.02 lb	3,500	TSP-30KG	26 lb / 11.8 kg	809161191608
		31 kg	0.01 kg	3,500			
APS150	12 in x 14 in / 31 cm x 36 cm	150 lb	0.05 lb	3,000	TSP-100KG	33 lb / 15 kg	809161191707
		60 kg	0.02 kg	3,000			
APS250	18 in x 18 in / 46 cm x 46 cm	250 lb	0.1 lb	2,500	TSP-100KG	55 lb / 25 kg	809161191806
		113 kg	0.05 kg	2,500			

Power Supply: 100-240 VAC 50/60Hz 12 VDC 1A wall plug-in UL/CSA listed AC power adapter included (Cardinal part no. 6800-1045)

Display: 5-digit, 7-segment, 0.875-in / 22-mm high backlit bright green LCD with 0.71-in / 18-mm high digits

Interfaces: 3 RS-232 serial (1 RS-232 cable included), 1 USB-B, OPOS compatible, most POS system protocols included (Cardinal Scale/SMA, NCI/Worldship, Mettler PS, Mettler SICS)

Construction: Stainless steel weighing platform, ABS plastic indicator and mounting bracket, and steel base (APS70/150/250) or aluminum base (APS8/10/12/160/15/20/30)

Included: (1) 4-ft / 122-cm RS-232 serial cable, (1) AC power adapter, and CD-ROM with operation manual and USB driver

Detecto Scale reserves the right to improve, enhance, or modify features and specifications without prior notice.



102 East Daugherty St., Webb City, MO 64870 USA
Toll-Free: (800) 641-2008 E-mail: detecto@cardet.com
www.Detecto.com

SOLD BY: