



Gas Hoses

HG-2E-72




TAG:

SAFET-LINK Gas Hose

Architect/Engineering Specifications:

72" coated gas appliance connector hose with 1" NPT male connections. Certified to ANSI Z21.69/CSA 6.16 and NSF 2.

Job Name _____
Model Specified _____ Quantity _____
Variations Specified _____
Date _____



90° Elbows



Features & Benefits:

- 72" coated gas appliance connector
- 1" NPT male freespun inlet
- 1" NPT male freespun outlet
- (2) 90° elbows included
- 360° rotatable hex nut rotates completely and freely
- Optimum torsional relief improves safety, increases connector life
- Provides efficient, full gas flow
- Material: Extruded coated stainless steel braids

Product Compliance:

- ANSI Z21.69 / CSA 6.16
- NSF 2
- NFPA 54

Warranty: Five Year (Limited)

Performance Data:

- Gas Pressure: 1/2 psi max
- Temperature: 350° F max
- Capacity: 348,000 BTU/ hr min



T&S BRASS AND BRONZE WORKS, INC.



• 2 Saddleback Cove • Travelers Rest, SC 29690
Ph 800-476-4103 • Fax 864-834-3518
• Simi Valley, CA • Ph 800-423-0150 • www.tsbrass.com

Date: 10/09/15