

SAFE-T-LINK® GAS CONNECTORS

WELDED FITTINGS:

Will not pull off under stress

FREESPIN FITTING:

360-degree rotation prevents twisting of hose during appliance movement

EXTRUDED COATING:

Unlike dipped coatings, does not intrude on braid and maintains even thickness for strength and flexibility

SWIVELINK SWIVEL:

Increased mobility and space savings

STRESS-LITE CORRUGATED HOSE:

Reduced stress on inner tube boosts flexibility and durability

YELLOW COLOR:

Complies with ASME A 13.1 color designation for hazardous materials

STAINLESS STEEL BRAIDED HOSE:

Machine braided tight fit provides increased tensile strength vs. gapped braid

OPTIONAL QUICK-DISCONNECTS:

Available for wall and appliance ends

MULTIPLE SIZE OPTIONS:

24" to 72" lengths and ½" NPT to 1" NPT internal thread and diameters

LEADING HOSE STRENGTH:

Requires 64% more force to kink hose vs. competitors

LONG-LASTING DURABILITY:

Last 2.5 times as long as competitors in appliance pull-away tests



AVAILABLE ACCESSORIES
support application needs and increased safety compliance



SUPERIOR CONSTRUCTION
for safety and performance



SAFE-T-GUARD®
safety shut-off valve prevents gas flow when disconnected



5-YEAR WARRANTY



POSI-SET
wheel placement system available