

# BAKERY DISPLAY CASES NATURAL Refrigerant

## Self-Cleaning Condenser Equipped Units

### ■ Self-Cleaning Condenser (Patented)

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

### ■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

### ■ Attractive, elegant, glass sided Euro design

Straight, tempered front & side glass with minimal frame provide full product visibility to optimize display effects. Its elegant contemporary euro design and luxurious colored case will not only enhance any store atmosphere but also will keep product presentation at its best and most beautiful.

### ■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

### ■ Digital temperature controller

### ■ Double pane glass is tempered for safety (Front heated glass)

### ■ Adjustable, tempered glass shelf with AL front and back edges

### ■ Stainless steel airflow grille

### ■ Sliding rear doors for product loading & unloading



Self-Cleaning Condenser  
Maintenance-free  
during warranty period  
**TBP36-46NN-S**



**TBP36-54NN-B**

### ■ Rear access to compressor compartment for quick and easy service

### ■ Stainless steel color option available

### ■ Standard features

- No plumbing required
- Safety shielded LED interior lighting
- White and black colors come standard
- 3" dia. swivel casters with locks on the rear set

### - Recommended operating conditions

TBP models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively.

## TBP-NN MODELS SPECIFICATIONS

| ELECTRICAL/DIMENSIONAL DATA       | TBP36-46NN-W(B, S)       | TBP48-46NN-W(B, S)       | TBP60-46NN-W(B, S)   |
|-----------------------------------|--------------------------|--------------------------|----------------------|
| Voltage                           | 115/60/1                 | 115/60/1                 | 115/60/1             |
| Plug Type                         | ① NEMA 5-15P             | ① NEMA 5-15P             | ① NEMA 5-15P         |
| Full Load Amp.                    | 6                        | 6.3                      | 6.5                  |
| Compressor HP                     | 1/3                      | 3/4                      | 3/4                  |
| Refrigerant                       | R-290                    | R-290                    | R-290                |
| Net Capacity (cu. ft.)            | 9                        | 12.4                     | 15.7                 |
| Ext. Dimension (L x D x H*) (in.) | 35 3/8 x 27 1/2 x 44 1/8 | 47 1/4 x 27 1/2 x 44 1/8 | 59 x 27 1/2 x 44 1/8 |
| # of Shelves                      | 1                        | 1                        | 1                    |
| Shelf Size (L x D) (in.)          | 31 3/8 x 13              | 43 1/4 x 13              | 55 x 13              |
| Net / Gross Weight (lbs.)         | 317 / 494                | 383 / 582                | 445 / 665            |

  

| ELECTRICAL/DIMENSIONAL DATA       | TBP36-54NN-W(B, S)       | TBP48-54NN-W(B, S)       | TBP60-54NN-W(B, S)   |
|-----------------------------------|--------------------------|--------------------------|----------------------|
| Voltage                           | 115/60/1                 | 115/60/1                 | 115/60/1             |
| Plug Type                         | ① NEMA 5-15P             | ① NEMA 5-15P             | ① NEMA 5-15P         |
| Full Load Amp.                    | 6                        | 6.5                      | 6.8                  |
| Compressor HP                     | 1/3                      | 3/4                      | 3/4                  |
| Refrigerant                       | R-290                    | R-290                    | R-290                |
| Net Capacity (cu. ft.)            | 12.5                     | 17.2                     | 21.8                 |
| Ext. Dimension (L x D x H*) (in.) | 35 3/8 x 27 1/2 x 52 1/8 | 47 1/4 x 27 1/2 x 52 1/8 | 59 x 27 1/2 x 52 1/8 |
| # of Shelves                      | 2                        | 2                        | 2                    |
| Shelf Size (L x D) (in.)          | 31 3/8 x 13, 31 3/8 x 11 | 43 1/4 x 13, 43 1/4 x 11 | 55 x 13, 55 x 11     |
| Net / Gross Weight (lbs.)         | 362 / 550                | 433 / 643                | 505 / 741            |

Design and specifications subject to change without notice. Most updated spec sheets are available at [www.turboairinc.com](http://www.turboairinc.com).

Actual shipping weight may differ due to extra packing materials for product protection.

\* Height does not include 2-1/4" for caster height.

### ■ WARRANTY: 2 Year Parts and Labor Warranty, 5 Year Compressor Warranty