

G150

INSTALLATION CHECKLIST

GAGGIA
MILANO


GENERAL MACHINE ENVIRONMENT

- ☐ The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
- ☐ The counter accommodates the machine size and weight:
 - Dimensions: 14.5" (W) x 31" (H) x 23.1" (D)
 - Dimensions with NSF/ANSI 4 legs: 14.5 (W) x 33.6 (H) x 23.1 in (D)
 - Weight: 104 lb
- ☐ An access hole has been pre-drilled in the counter for drainage and power in accordance with model installation template
- ☐ Hole in counter is fitted with a collar to protect electrical cord, water line & drain tube.
- ☐ Machine can safely be installed with a minimum clearance of 1 5/8 inch from the back wall.

ELECTRICAL REQUIREMENTS

G150 Specifications	120/240 V, 60 Hz, 3690 W NEMA L14-30 Plug
----------------------------	--

- ☐ Power outlet receptacle is NEMA L14-30R.
- ☐ Dedicated electrical circuit meets the G150 power requirements.
- ☐ No extension cord or power strip on the circuit.



WATER SPECIFICATIONS

Pressure & Hardness

- ☐ Pressure is between 21.7 PSI and 123.28 PSI.
- ☐ pH range is between 6.5 and 7.5.
- ☐ Hardness (TDS) is between 89 PPM and 142 PPM.
- ☐ Machine water line is equipped with softness/filtration system and descaling device.

Water Network

- ☐ The water network provides cold, drinkable tap water.
- ☐ Dedicated 3/8" diameter water line.
- ☐ Shutoff valve with a 3/8" compression fitting on machine's end.

HIGHLY RECOMMENDED: Connection to a floor drain in accordance with local health code.