



# BEVERAGE-AIR

Project: _____	AIA#
Item: _____	
Location: _____	SIS#
Approved: _____	

**HBRF23HC BOTTOM MOUNT DUAL TEMPERATURE REFRIGERATOR/FREEZER**

## DUAL TEMPERATURE REFRIGERATOR/FREEZER

### HBRF23HC Half-Solid Door Bottom Mount Reach-In

Hydrocarbon Series

**MODEL:**  
**HBRF23HC-1-A**



**3 Year Parts / Labor Warranty**  
**Additional 4 Year Compressor Warranty**

#### CABINET CONSTRUCTION

- Stainless steel front, side, and grille (galvanized back & bottom)
- Stainless steel interior
- Full electronic control with one-touch defrost
- Dual temp refrigerator/freezer units provide two different operating temperature zones for different types of products
- Refrigerator is the top section
- Freezer is the bottom section
- One-piece grille allows easy removal/installation for preventative maintenance
- Door locks
- Self closing doors, 120° stay open feature with spring-loaded style hinges
- Snap-in magnetic door gaskets for easy cleaning and replacement
- Four (4) heavy-duty epoxy coated wire shelves
- LED lighting standard
- 6" Heavy-duty casters with (2) brakes
- Certified for open food product

#### OPTIONS & ACCESSORIES

- Epoxy shelves
- Shelf clips
- 3" Casters or 6" legs
- Wine temperature control
- Door swing orientation (at time of order)
- Remote option\* (see note on back page)

#### REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Adaptive defrost
- Epoxy coated evaporator coil
- Refrigerator maintains product temperatures between 36°F to 38°F
- Freezer maintains product temperature to -10°F



Please verify qualifying units by visiting:  
[www.energystar.gov/cfs](http://www.energystar.gov/cfs)

3779 Champion Blvd., Winston-Salem, NC 27105  
1-888-845-9800 Fax: 1-336-245-6453  
Beverage-Air.com Sales@bevair.com



# BEVERAGE-AIR

## Dual Temp Bottom Mount Reach-In Half-Solid Door Refrigerator/Freezer Model: HBRF23HC-1-A

MODEL		HBRF23HC-1-A
<b>EXTERNAL DIMENSIONAL DATA</b>		
Width Overall		27 ¼"
Depth Overall (with handles)		33 ¾"
Height Overall (with casters)		84"
Number of Doors/Shelves		2 / 4
Depth with Door Open 90°		57 ⅝"
Door Openings (in)		24 ⅙" x 24 ⅝"
<b>INTERNAL DIMENSIONAL DATA</b>		
NET Capacity (cubic ft.)	(R) 8.65 (F) 11.50	
Internal Width Overall (in)		24 ¼"
Internal Depth Overall (in)		28 ¼"
Internal Height Top Usable (in)		26 ⅝"
Internal Height Bottom Usable (in)		17 ⅞"
<b>ELECTRICAL DATA</b>		
Full Load Amperes	(R) 2.0 (F) 4.0	
<b>REFRIGERATION DATA</b>		
Horsepower	(R) 1/10 (F) 1/2	
Capacity (BTU/Hr)	(R) 1110 (F) 1513	
Heat Rejection (BTU/Hr)	3934.5	
Charge (lbs/grams)	(R) 0.992/45 (F) 0.1213/55	
<b>SHIPPING DATA</b>		
Gross Weight - Crated		446 lbs
Height - Crated		87"
Width - Crated		29"
Depth - Crated		38"

\*NOTE: Remote units are field wired and come with 6" legs.  
Refrigerant must be specified at time of order.

### Model Views

Required Clearance: Top 0", Bottom 3", Rear 3", Sides 0"

**PLAN VIEW**

**ELEVATION VIEW**

**SIDE VIEW**

### ELECTRICAL CONNECTION



115/60/1  
(2) NEMA 5-15P  
Units pre-wired at  
factory and include 8'  
long cord and plug set.

