

Ergo-One® SYSTEM UTILITY CARTS | STAINLESS STEEL

This beneficial cart was designed with the help of an orthopedic specialist to prevent body strain and unnecessary worker's comp expenses.

- Shelf heights are within a "Safety Zone" that is the proper range for loading and unloading, bottom shelf is 20" (508) from the floor
- No-mark cushion tread wheels absorb impact, reducing vibration and strain
- 20-gauge stainless steel shelves are reinforced for added strength
- All welded construction for structural strength and easier-to-clean surface
- Stainless Steel is easy to clean and sanitize

FACTORY INSTALLED OPTIONS (PAGE 55):

- · Lake-Glide casters and wheels
- Ergonomic Handle Grips and Bumpers, Blue
- Handle Set Both Ends
- Strip and offset perimeter bumper
- 2 Brake Casters
- 4 5" Swivel Casters
- 2 5" Swivel, 2 5" Fixed Casters
- 2 5" Swivel, 2 -5" Fixed
- High-Temp Nylon Casters

THE **SAFETY** ZONE

Ergo-One* shelf heights are in the "safety zone" for loading and lifting—the bottom shelf is 20" (508mm) from the floor; the top shelf is 35-3/4" (867 mm) from the floor to prevent back strains.



	# of	Shelf	Shelf	Top Shelf	Overall Size			Caston	Caston	Case Weight	Case Cube	Feder
Model	Shelves	Size	Clearance	Height*	W	L	H**	- Caster Type	Caster Dia.	Lbs. (Kg)	Cu. ft. (m ³)	ups
6800	2	15- 1/2" x 24" (394 x 610)	14-1/8" (359)	35-1/4" (895)	16-1/2" (419	28" 711	44-3/8" 1127)	All swivel, No-Mark, cush- ion tread	5" (127)	32 (14.5)	25.6 (.99)	OK
6810	2	18" x 27" (457 x 686)	14-1/8" (359)	35-1/4" (895)	19" (483	31-1/8" 791	44- 3/8" 1127)	All swivel, No-Mark, cush- ion tread	5" (127)	35 (15.9)	16.3 (.63)	NA
6820	2	21" x 35" (533 x 889)	14-1/2" (368)	35-3/4" (908)	22" (559	39-1/8" 994	44- 3/8" 1127)	All swivel, No-Mark, cush- ion tread	5" (127)	61 (27.6)	23.2 (.90)	NA
6830	2	21" x 49" (533 x1245)	14-1/2" (368)	35-3/4" (908)	22" (559	53-1/8" 1400	44- 3/8" 1127)	2 swivel, 2 fixed, No-Mark, cushion tread	5" (127)	128 (58.2)	80.1 (3.1)	NA

Measurements in () denote metric millimeters, unless otherwise specified. *Measured from floor. **Includes height of ergonomic handles. Handle assembly required. Model 6800 caster assembly required.

