



eLakesideFoodservice.com/modifiable

ADJUST-A-FIT® TUBULAR FRAME PLATE DISPENSERS | STAINLESS STEEL

The convenience and mobility of an Adjust-A-Fit® cabinet in a tubular frame design.

- Lightweight open tubular frame design for backof-the-house applications
- Adjust-a-fit diameter hand adjustment of 3 1/4" (83) allows flexibility for varying dish sizes
- Adjusting height level is easy and convenient.
 Simply detach and attach springs as needed with no tools required
- Easy glide design is non-stick for smooth operation
- Heated models feature individual thermostatic controls for heat regulation flexibility
- All 4" swivel casters, 2 with brake, allow easy maneuverability. Extra load casters provide additional support for full dispensers
- Stainless steel material is easy to clean and sanitize

FACTORY INSTALLED OPTIONS):

• Round corner bumpers

ACCESSORIES (PAGE 79):

• Stainless Steel Dish Covers







Ships in: 4 days or less!



Non-Heated Model	Case Wt Lbs. (Kg)	Case Cube Cu. ft. (m³)	Heated Model	Case Wt Lbs. (Kg)	Case Cube Cu. ft. (m³)	Accom. Plate Size	Overall Size		
							W	L	Н
Stack									
772	87 (39.5)	21.5 (.61)	776	93 (42.2)	21.5 (.8)	4-1/4" to 7-1/2" (108 to 191)	17-3/4" (451	35-1/2" 902	38-5/16" 989)
773	95 (43.1)	21.5 (.61)	777	102 (46.3)	21.5 (.8)	6-1/2" to 9-3/4" (165 to 248)	17-3/4" (451	35-1/2" 902	38-5/16" 989)
774	105 (47.6)	21.5 (.61)	778	113 (51.3)	21.5 (.8)	8-3/4" to 12" (222 to 305)	17-3/4" (451	35-1/2" 902	38-5/16′ 989)
Stack									
782	119 (54)	28.1 (.8)	786	127 (57.6)	28.1 (.8)	4-1/4" to 7-1/2" (108 to 191)	17-3/4" (451	45-3/4" 1162	38-5/16" 989)
783	129 (58.5)	28.1 (.8)	787	139 (63.1)	28.1 (.8)	6-1/2" to 9-3/4" (165 to 248)	17-3/4" (451	45-3/4" 1162	38-5/16′ 989)
784	142 (64.4)	28.1 (.8)	788	153 (69.4)	28.1 (.8)	8-3/4" to 12" (222 to 305)	17-3/4" (451	52-1/2" 1334	38-5/16" 989)
Stack	•								
792	141 (64)	25.8 (.7)	796	147 (66.7)	25.8 (.7)	4-1/4" to 7-1/2" (108 to 191)	31" (787	31" 787	38-5/16" 989)
793	153 (69.4)	25.8 (.7)	797	161 (73)	25.8 (.7)	6-1/2" to 9-3/4" (165 to 248)	31" (787	31" 787	38-5/16′ 989)

Measurements in () denote metric millimeters, unless otherwise specified. Lake-Glide* Casters: 4*(102) - All swivel, 2 ea. w/brake. Heated Models include 6'(1829) cord with 5-15P NEMA plug for use with 120 V except Model 797 (5-20P)