

## Blixer® 20 Special Order\*

\*Extended lead time may apply



20 L



A

## SALES FEATURES

**Blixer 20** is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

B

## TECHNICAL FEATURES

**Blixer 20.** 3-phase. Power 5.5 HP. 2 speeds. Pulse function. 20 L stainless-steel bowl with 2 handles. Bowl-base blade assembly with 3 detachable fine serrated blades included. Scraper arm and lid wiper included. 15 to 65 portions (7 oz.) and more.

Select your options at the back page, **F** part.

C

## TECHNICAL DATA

Output power	5.5 HP
Electrical data	208-240V/60/3 - 21.3 Amp
Speeds	1800 and 3600 rpm
Dimensions (WxDxH)	14 15/16" x 24 13/16" x 30 3/4" - Cube: 11.71
Rate of recyclability	95%
Net weight	160 lbs
Nema #	L15-30P
Reference	BLIXER 20 - 208-240V/60/3

D

Number of 7 oz portions :

15 to 65 portions

Quantity processed per operation

6 to 28 lbs

E

## PRODUCT FEATURES / BENEFITS

## MOTOR BASE

- **Direct drive induction motor (no belt)** for intensive use.
- Power 5.5 HP.
- Stainless steel motor shaft.
- Flat, easy-clean motor base.
- IP65 control panel with flush buttons.
- Magnetic safety and motor brake.
- **2 speeds : 1800 and 3600 rpm**
- Pulse function for a better cut precision.

## CUTTER FUNCTION

- 20 L stainless-steel bowl with 2 handles for a better grip.
- Central bowl locking system for easy assembly.
- Bowl-base blade assembly with 3 fine serrated blades to ensure a perfectly uniform consistency, even when processing small quantity.
- Transparent lid to enable user to monitor processing.
- **Transparent lid with bowl scraper** to improve the end-product consistency and **with a lid wiper** to enable user to monitor processing.
- **Opening in center of lid** for adding liquid or dry ingredients during processing.

## INCLUDED ACCESSORIES

- Stainless steel fine serrated blade assembly (3 blades)
- Scraper arm and lid wiper

## STANDARDS

ETL electrical and sanitation Listed/ cETL (Canada)



## Blixer® 20

**F**

## OPTIONAL ATTACHMENTS

- 3 Blade Fine Serrated Edge Stainless Steel Adjustable Blade Assembly - Ref. 57102
- Lid Assembly with seal - Ref. 59362
- Complete Bowl Assembly - Ref. 59267

**G**

## ELECTRICAL DATA

208-240V/60/3 – delivered with cord and plug.

