

C 80



D

Output

up to 165 lbs. per hour

A

SALES FEATURES

Automatic Sieves C 80 is designed to strain preparations (sauce base, bisque, fish soup), to separate fibers from vegetables and to extract pulp from fruits.

B

TECHNICAL FEATURES

AUTOMATIC SIEVES C80 Single phase. Power 3/4 HP. 1 speed. Table top model. 100% stainless-steel construction. 1 perforated basket Ø 1 mm (1/32") included (other baskets available in option). Continuous feed hopper. Continuous end-product and waste ejection chute. Model with an output from up to 165 lbs. per hour.

Select all the options at the back page, **F** part.

C

TECHNICAL DATA

Output power	3/4 HP
Electrical data	Single phase - Plug included
Speed	1725 rpm
Dimensions (HxLxW)	21 1/2" x 24 3/8" x 14 1/8"
Rate of recyclability	95%
Net weight	48 lbs
Reference	C 80 - 120V/60/1

E

PRODUCT FEATURES/BENEFITS

MOTOR BASE

- **Induction direct drive motor** for intensive use.
- Power 3/4 HP.
- 100% stainless-steel construction.
- Magnetic safety and motor brake.
- **1 speed : 1725 rpm.**

SIEVE FUNCTION

- **Continuous feed hopper** of washed products, no need to remove seeds, to stone or peel for ease of use and time saving.
- **Continuous end-product ejection chute** : fruit and vegetable puree, coulis, soup...
- **Continuous waste ejection chute** : skins, pits, seeds, tails, bones, shells, fibres.
- Paddle assembly rotating at 1725 rpm to extract maximum pulp.
- All parts in contact with food are removable for a quick and easy cleaning.

INCLUDED ACCESSORIES

- 1 Perforated basket Ø 1 mm (1/32") : for finely sieving

STANDARDS

ETL electrical and sanitation Listed/ cETL (Canada)




C 80

F

OPTIONS

- 1 Perforated basket \varnothing 0.5 mm (1/64") - Ref. 57009
- 1 Perforated basket \varnothing 3 mm (1/8") - Ref. 57008
- Additional rubber scraper (per unit) - Ref. 100338



G

ELECTRICAL DATA

