

CL 52



SALES FEATURES

The CL52 Vegetable Preparation Machine is ideal for slicing, ripple cutting, grating, dicing, shredding and making french fries from all types of fruit and vegetables, as well as grating cheese.

B TECHNICAL FEATURES

The CL52 Vegetable Preparation Machine — Single-phase. Power - 2 HP. Speed 425 rpm. Magnetic safety system, motor brake and lever-activated auto restart. This metal Vegetable Preparation Machine has a lateral ejection facility and is equipped with Two hoppers in one head - one large full moon hopper for cutting large products and 1 cylindrical hopper: Ø 2½" and/or Ø 1,5". Stainless steel motor base, chute and continuous feed lead. D-Clean Kit. Suitable for 70 to 600 covers per service. 2 discs included: 28064W (3mm) 1/8" slicing disc and 28058W (3mm) 1/8" grating disc. Large range of 52 Mineral+ discs available as option: easy cleaning, dishwasher resistant.

Select your options at the back page **F** part.

| C | TECHNICAL DATA |
|-----------------------|--------------------------------------|
| Output power | 2 HP |
| Electrical data | Single-phase - 9.4 Amp plug included |
| Speed | 425 rpm |
| Dimensions (H×L×W) | 27 3/16" x 13 3/8" x 14 3/16" |
| Rate of recyclability | 95% |
| Net weight | 59 lbs |
| Nema # | 5-15P |
| Reference | CL 52 E 120V/60/1 |

Number of meals per service 70 to 600 Theoretical output per hour* 1655 lbs

PRODUCT FEATURES / BENEFITS

MOTOR BASE

- Industrial induction motor for intensive use.
- Power 2 HP
- · Stainless steel motor base and shaft.
- Magnetic safety system with motor brake.
- Speed 425 rpm

VEGETABLE PREPARATION FUNCTION

- Vegetable Preparation Machine equipped with 2 hoppers:
- 1 large full moon hopper for cutting large products (will accommodate whole heads of cabbage and lettuce).
- 1 cylindrical hopper for long, delicate vegetables. The Exactitube pusher can be used to reduce the diameter of the hopper for cutting up small ingredients.
- · Removable continuous feed lead.
- · Reversible discharge plate for processing delicate produce.
- Lateral ejection facility for space-saving and greater user comfort, and accommodates 7 7/8 inch high gastronorm pans.
- Lever-activated auto restart (by the pusher).
- Lever-assisted facility requires less effort from the operator and increases output.
- Vertical pusher pressure exerted on vegetables to ensure uniform cuts.
- Large range of 52 Mineral+ discs available as option: easy cleaning, dishwasher resistant.
- 2 discs included: 28064W (3mm) 1/8" slicing disc and 28058W (3mm) 1/8" grating disc.
- Stainless steel blades on slicing discs, blades on Julienne discs and grating discs are removable.
- 3 positions for optimum operator comfort. Lever-activated auto restart.
- . Brush to facilitate cleaning of motor shaft.
- . D-Clean Kit to facilitate cleaning of dicing grids.

MASHED POTATO FUNCTION

· option: Mashed Potato Kit

STANDARDS

ETL electrical and sanitation Listed/ cETL (Canada)



Update: May 2024

* Results may differ depending on the type of the hopper used, the choice of the cut and the setup of the workstation.

Specification sheet www.robot-coupe.com



CL 52

F OPTIONAL ACCESSORIES

- EasyClean Xpress 8x8mm Ref. 49305
- EasyClean Xpress 10x10mm Ref. 49309
- EasyClean Xpress 12x12mm Ref. 49313
- EasyClean Xpress 14x14mm Ref. 49314
- Wall 8-disc holder Ref.107812
- Motor shaft brush Ref. 49257
- 3 mm potato ricer equipment Ref. 28208

| | SUGGESTED PACKS OF DISCS |
|--------------------|---|
| 3 disc package | 5mm (3/16") coarse grating, 6mm (1/4"x 1/4") julienne and 5mm (3/16") slicing discs. |
| 5 disc package | 5mm (3/16") coarse grating; 6mm (1/4"x1/4") julienne; 5mm (3/16"), 10mm (3/8") slicing discs; 10x10mm (3/8" x 3/8") dicing grid |
| 16 disc package | Slicers - 0.8mm (1/32"), 2mm (5/64") & 5mm (3/16". 2 graters - 2mm (5/64") & 5mm (3/16"); 3 dicing - 5x5x5mm (3/16"), 10x10x10mm (3/8") & 14x14x5mm (9/16"x9/16"x3/16"). 2 Julienne sticks - 2.5 x 2.5mm (1/10"x1/10") & 2 x 10mm (5/64"x3/8"). Dice Cleaning Kit and 2 disc holders. |



| | SLICERS | |
|----------------------|---------|--------|
| 0.6 mm | | 28166W |
| 0.8 mm | | 28069W |
| 1 mm (1/32") | | 28062W |
| 2 mm (5/64") | | 28063W |
| 3 mm (1/8") | | 28064W |
| 4 mm (5/32") | | 28004W |
| 5 mm (3/16") | | 28065W |
| 6 mm (1/4") | | 28196W |
| 8 mm (5/16") | | 28066W |
| 10 mm (3/8") | | 28067W |
| 14 mm (9/16") | | 28068W |
| 20 mm (25/32") | | 28132W |
| 25 mm (1") | | 28133W |
| cooked potatoes 4 mm | (5/32") | 27244W |
| cooked potatoes 6 mm | (1/4") | 27245W |



| | RIPPLE CUTTING | |
|--------------|----------------|--------|
| 2 mm (5/64") | | 27068W |
| 3 mm (1/8") | | 27069W |
| 5 mm (3/16") | | 27070W |



| GRATERS | |
|-------------------|--------|
| 1.5 mm (1/16") | 28056W |
| 2 mm (5/64") | 28057W |
| 3 mm (1/8") | 28058W |
| 4 mm (5/32") | 28136W |
| 5 mm (3/16") | 28163W |
| 7 mm (9/32") | 28164W |
| 9 mm (11/32") | 28165W |
| Röstis potatoes | 27164W |
| Raw potatoes | 27219W |
| Fine Pulping disc | 28055W |
| Hard Cheese grate | 28061W |



| JULIENNE | |
|-----------------------------------|--------|
| 1x8 mm tagliatelle (1/32"x5/16") | 28172W |
| 1x26 onion/cabbage (1/32"x1 1/4") | 28153W |
| 2×2 mm (5/64" x 5/64") | 28051W |
| 2×4 mm (5/64" × 5/32") | 27072W |
| 2×6 mm (5/64" × 1/4") | 27066W |
| 2×8 mm (5/64" × 5/16") | 27067W |
| 2x10 tagliatelle (5/64"x3/8") | 28173W |
| 2.5×2.5 mm (1/10" × 1/10") | 28195W |
| 3×3 mm (1/8" × 1/8") | 28101W |
| 4×4 mm (5/32" × 5/32") | 28052W |
| 6×6 mm (1/4" × 1/4") | 28053W |
| 8×8 mm (5/16" × 5/16") | 28054W |



| DICING EQUIPMENT | |
|--|--------|
| 5×5 mm (3/16") | 28110W |
| 8×8 mm (5/16") | 28111W |
| 10×10 mm (3/8") | 28112W |
| 12x12 mm (15/32") | 28197W |
| 14x14x5 mm Mozzarella (9/16"x9/16"x3/16") | 28181W |
| 14x14x10mm (9/16"x9/16"x3/8") | 28179W |
| 14×14 mm (9/16") | 28113W |
| 20×20 mm (25/32") | 28114W |
| 25×25 mm (1") | 28115W |
| 2" Lettuce Cut | 28180W |



| FRENCH FRY EQUIPMENT | |
|------------------------|--------|
| 8x8 mm (5/16" x 5/16") | 28134W |
| 8x16 mm (5/16""x 5/8") | 28159W |
| 10x10 mm (3/8"x 3/8") | 28135W |
| 10x16 mm (3/8" x 5/8") | 28158W |

ELECTRICAL DATA

120V/60/1 - delivered with cord and plug.







