



Camshelving® Elements XTRA Series

Mobile Starter Units 4 or 5 Vented Shelves

HEIGHTS	DEPTHS	LENGTHS	
2	3	5	
70 ¼"	18"	36"	54"
78 ¼"	21"	42"	60"
	24"	48"	

- Mobile Starter Units include:**

2 factory assembled mobile post kits, 8 or 10 shelf traverses, traverse dovetails, shelf plates and 4 premium swivel casters with total locking brake.

All units ship complete in 1 box.



Features & Benefits

- Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Withstands storage temperatures -36° to 190°F (-38° to 88°C). Impervious to moisture, chemicals, salt, food acids and humidity.
- Posts and traverses are made of a revolutionary, extremely strong composite material with a smooth, easy to clean surface. Stronger than common wire shelving and lighter in weight than Camshelving Premium Series. Traverse dovetails are separate from the posts and attach easily to secure the shelf traverses.
- Premium caster is made of highly durable, non-corrosive plastic with a 5" (12,7 cm) swivel, non-marking thermoplastic rubber wheel. Total locking brake locks both swivel motion and the wheel.
- Optional donut bumper offers added protection during transport and when maneuvering mobile units into place against walls or alongside other units for storage.
- Smooth polypropylene shelf plates contain Camguard, an antimicrobial technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation.
- Posts and traverses wipe clean. Traverses and shelf plates remove easily for cleaning.
- Shelf traverses can be removed and adjusted at 4" (10,2 cm) increments.
- Requires some assembly with minimal parts. Use a rubber mallet only.
- Lifetime warranty against rust and corrosion (posts, traverses and shelf plates).
- Available in 1 color – Speckled Gray (480).

Project _____

Item No. _____

Model No. _____

Quantity _____



Mobile Starter Unit with
4 Vented Shelves



Mobile Starter Unit with
5 Vented Shelves

WEIGHT BEARING CAPACITY

Weight must be evenly distributed across the entire shelf.

		UNIT LENGTH 36" – 60"
MOBILE UNIT	Unit only*	750 lbs.

* Due to the weight bearing capacity of casters, maximum weight load on an entire Mobile Unit is 750 lbs. (340 kg).

Approvals



COMPONENT

Post Connectors, Corner Connectors, Floor Fastener, Wall Fastener, Identification Tags, Shelf Rails, Single Shelf Security Cage, Peg Board and Shelf Divider Bars are not NSF listed.



www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.

Telephone: (714) 848-1555 Toll Free: (800) 854-7631 Customer Service: (800) 833-3003


© Cambro Manufacturing Company Huntington Beach, California 92647

Printed in U.S.A. 09/23

Camshelving® Elements XTRA Series

Mobile Starter Units 4 or 5 Vented Shelves

70 1/4"
HEIGHT



18"
DEPTH

21"
DEPTH

24"
DEPTH

78 1/4"
HEIGHT

18"
DEPTH

21"
DEPTH

24"
DEPTH

V4 4-Shelf Vented Mobile Units

CODE	DIMENSIONS D x L x H*
EXMU183670V4	18" x 36" x 70 1/4"
EXMU184270V4	18" x 42" x 70 1/4"
EXMU184870V4	18" x 48" x 70 1/4"
EXMU185470V4	18" x 54" x 70 1/4"
EXMU186070V4	18" x 60" x 70 1/4"
EXMU213670V4	21" x 36" x 70 1/4"
EXMU214270V4	21" x 42" x 70 1/4"
EXMU214870V4	21" x 48" x 70 1/4"
EXMU215470V4	21" x 54" x 70 1/4"
EXMU216070V4	21" x 60" x 70 1/4"
EXMU243670V4	24" x 36" x 70 1/4"
EXMU244270V4	24" x 42" x 70 1/4"
EXMU244870V4	24" x 48" x 70 1/4"
EXMU245470V4	24" x 54" x 70 1/4"
EXMU246070V4	24" x 60" x 70 1/4"

CODE	DIMENSIONS D x L x H*
EXMU183678V4	18" x 36" x 78 1/4"
EXMU184278V4	18" x 42" x 78 1/4"
EXMU184878V4	18" x 48" x 78 1/4"
EXMU185478V4	18" x 54" x 78 1/4"
EXMU186078V4	18" x 60" x 78 1/4"
EXMU213678V4	21" x 36" x 78 1/4"
EXMU214278V4	21" x 42" x 78 1/4"
EXMU214878V4	21" x 48" x 78 1/4"
EXMU215478V4	21" x 54" x 78 1/4"
EXMU216078V4	21" x 60" x 78 1/4"
EXMU243678V4	24" x 36" x 78 1/4"
EXMU244278V4	24" x 42" x 78 1/4"
EXMU244878V4	24" x 48" x 78 1/4"
EXMU245478V4	24" x 54" x 78 1/4"
EXMU246078V4	24" x 60" x 78 1/4"


Color: Speckled Gray (480).
*Includes 127 mm casters.

Project _____

Item No. _____

Model No. _____

Quantity _____



18"
DEPTH

21"
DEPTH

24"
DEPTH

V5 5-Shelf Vented Mobile Units

CODE	DIMENSIONS D x L x H*
EXMU183670V5	18" x 36" x 70 1/4"
EXMU184270V5	18" x 42" x 70 1/4"
EXMU184870V5	18" x 48" x 70 1/4"
EXMU185470V5	18" x 54" x 70 1/4"
EXMU186070V5	18" x 60" x 70 1/4"
EXMU213670V5	21" x 36" x 70 1/4"
EXMU214270V5	21" x 42" x 70 1/4"
EXMU214870V5	21" x 48" x 70 1/4"
EXMU215470V5	21" x 54" x 70 1/4"
EXMU216070V5	21" x 60" x 70 1/4"
EXMU243670V5	24" x 36" x 70 1/4"
EXMU244270V5	24" x 42" x 70 1/4"
EXMU244870V5	24" x 48" x 70 1/4"
EXMU245470V5	24" x 54" x 70 1/4"
EXMU246070V5	24" x 60" x 70 1/4"

CODE	DIMENSIONS D x L x H*
EXMU183678V5	18" x 36" x 78 1/4"
EXMU184278V5	18" x 42" x 78 1/4"
EXMU184878V5	18" x 48" x 78 1/4"
EXMU185478V5	18" x 54" x 78 1/4"
EXMU186078V5	18" x 60" x 78 1/4"
EXMU213678V5	21" x 36" x 78 1/4"
EXMU214278V5	21" x 42" x 78 1/4"
EXMU214878V5	21" x 48" x 78 1/4"
EXMU215478V5	21" x 54" x 78 1/4"
EXMU216078V5	21" x 60" x 78 1/4"
EXMU243678V5	24" x 36" x 78 1/4"
EXMU244278V5	24" x 42" x 78 1/4"
EXMU244878V5	24" x 48" x 78 1/4"
EXMU245478V5	24" x 54" x 78 1/4"
EXMU246078V5	24" x 60" x 78 1/4"

Optional Accessories

- ☐ Shelf Identification Tags
- ☐ Shelf Divider Panel
- ☐ Shelf Divider Bars (Straight or Angled)
- ☐ Shelf Rails
- ☐ Single Shelf Security Cage
- ☐ Shelf Traverses (Single or Double)
- ☐ Drying and Storage Cradles
- ☐ Universal Storage Rack
- ☐ Peg Board

Architect Specs

Posts and Traverses: Proprietary non-corrosive composite material.
Post Connectors: Reinforced polypropylene.
Shelf Plates: Reinforced polypropylene with Camguard® antimicrobial.
Caster: Non-corrosive plastic body and brake with non-marking thermoplastic rubber wheel.
Traverse Dovetails: Reinforced nylon.
Post Connector Collar Wedge: Reinforced nylon.

Approvals



COMPONENT

Post Connectors, Corner Connectors, Floor Fastener, Wall Fastener, Identification Tags, Shelf Rails, Single Shelf Security Cage, Peg Board and Shelf Divider Bars are not NSF listed.

CAMBRO®

www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.

Telephone: (714) 848-1555 Toll Free: (800) 854-7631 Customer Service: (800) 833-3003

© Cambro Manufacturing Company Huntington Beach, California 92647

Printed in U.S.A. 09/23

EXCS8

D082307