



## Camshelving® Elements XTRA Series

### Stationary Starter & Add-On Units 4 or 5 Vented Shelves

| HEIGHT | DEPTHS | LENGTHS |     |
|--------|--------|---------|-----|
| 1      | 3      | 8       |     |
| 84"    | 18"    | 24"     | 48" |
|        | 21"    | 30"     | 54" |
|        | 24"    | 36"     | 60" |
|        |        | 42"     | 72" |

- **Starter Units include:**  
2 factory assembled post kits, 8 or 10 shelf traverses, traverse dovetails and shelf plates.
- **Add-On Units include:**  
1 factory assembled post kit, 8 or 10 shelf traverses, traverse dovetails and shelf plates.

All units ship complete in 1 box.



#### Features & Benefits

- Designed to easily support the performance demands of a busy foodservice operation with medium to heavy storage needs.
- Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Withstands storage temperatures -36° to 190°F (-38° to 88°C). Impervious to moisture, chemicals, salt, food acids and humidity.
- Posts and traverses are made of a revolutionary, extremely strong composite material with a smooth, easy to clean surface. Stronger than common wire shelving and lighter in weight than Camshelving Premium Series. Traverse dovetails are separate from the posts and attach easily to secure the shelf traverses.
- Smooth polypropylene shelf plates contain Camguard, an antimicrobial technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation.
- Shelving Units interconnect in straight lines with shared posts. Uniquely engineered Post Connectors offer exceptional cross stabilization. Weight bearing is uncompromised and space is maximized. No add-on clips or "S" hooks required.
- Easily install heavy-duty Corner Connectors (front and back clasp design) to add shelves in corners or to install middle shelves between 2 units without any loss of weight bearing. Maximizes usable, easy access storage space.
- Posts and traverses wipe clean. Traverses and shelf plates remove easily for cleaning.
- Shelf traverses can be removed and adjusted at 4" (10,2 cm) increments.
- Sturdy reinforced nylon foot adjusts easily to level units.
- Requires some assembly with minimal parts. Use a rubber mallet only.
- Lifetime warranty against rust and corrosion (posts, traverses and shelf plates).
- Available in 1 color – Speckled Gray (480).

Project \_\_\_\_\_

Item No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_



Stationary Starter Unit



Stationary Starter and Add-On Unit

## WEIGHT BEARING CAPACITY

Weight must be evenly distributed across the entire shelf.

| SINGLE UNIT |                                  | UNIT LENGTH<br>24" – 60" | UNIT LENGTH<br>72" |
|-------------|----------------------------------|--------------------------|--------------------|
|             |                                  |                          |                    |
|             | Unit only                        | 2400 lbs.                | 2400 lbs.          |
|             | Shelf only                       | 800                      | 600                |
|             | Unit with dunnage stand*         | 2800                     | 2700               |
|             | Bottom shelf with dunnage stand* | 1200                     | 900                |

| CORNER UNIT<br>With 2 Dunnage<br>Stands required |                                   | UNIT LENGTH<br>24" – 60" |   |
|--------------------------------------------------|-----------------------------------|--------------------------|---|
|                                                  |                                   |                          |   |
|                                                  | Unit only                         | 2400                     | — |
|                                                  | Shelf only                        | 800                      | — |
|                                                  | Bottom shelf with dunnage stands* | 1200                     | — |

| INTERMEDIATE<br>SHELVES<br>Shelves Installed<br>Between 2 Units |                                   | UNIT LENGTH<br>24" – 60" |   |
|-----------------------------------------------------------------|-----------------------------------|--------------------------|---|
|                                                                 |                                   |                          |   |
|                                                                 | Unit only                         | 2400                     | — |
|                                                                 | Shelf only                        | 800                      | — |
|                                                                 | Bottom shelf with dunnage stands* | 1200                     | — |

\*Dunnage Stands add stability and increase weight bearing capacity on bottom shelf only. Add to any shelf length. Highly recommended for Starter Units 54" (1375 mm) and longer, all Corner Units, U-Shape Units and units specified for heavier loads.

#### Approvals



COMPONENT

Post Connectors, Corner Connectors, Floor Fastener, Wall Fastener, Identification Tags, Shelf Rails, Single Shelf Security Cage, Peg Board and Shelf Divider Bars are not NSF listed.



www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.

Telephone: (714) 848-1555 Toll Free: (800) 854-7631 Customer Service: (800) 833-3003

© Cambro Manufacturing Company Huntington Beach, California 92647

Printed in U.S.A. 09/23

# Camshelving® Elements XTRA Series

## Stationary Starter & Add-On Units 4 or 5 Vented Shelves

Project \_\_\_\_\_

Item No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_



### V4

#### 4-Shelf Vented Units

Starter

Add-On

**84"**  
HEIGHT



**18"**  
DEPTH

| LENGTH | CODE        |
|--------|-------------|
| 24"    | EXU182484V4 |
| 30"    | EXU183084V4 |
| 36"    | EXU183684V4 |
| 42"    | EXU184284V4 |
| 48"    | EXU184884V4 |
| 54"    | EXU185484V4 |
| 60"    | EXU186084V4 |
| 72"    | EXU188484V4 |

| LENGTH | CODE        |
|--------|-------------|
| 22"    | EXA182484V4 |
| 28"    | EXA183084V4 |
| 34"    | EXA183684V4 |
| 40"    | EXA184284V4 |
| 46"    | EXA184884V4 |
| 52"    | EXA185484V4 |
| 58"    | EXA186084V4 |
| 70"    | EXA187284V4 |

**21"**  
DEPTH

|     |             |
|-----|-------------|
| 24" | EXU212484V4 |
| 30" | EXU213084V4 |
| 36" | EXU213684V4 |
| 42" | EXU214284V4 |
| 48" | EXU214884V4 |
| 54" | EXU215484V4 |
| 60" | EXU216084V4 |
| 72" | EXU217284V4 |

|     |             |
|-----|-------------|
| 22" | EXA212484V4 |
| 28" | EXA213084V4 |
| 34" | EXA213684V4 |
| 40" | EXA214284V4 |
| 46" | EXA214884V4 |
| 52" | EXA215484V4 |
| 58" | EXA216084V4 |
| 70" | EXA218484V4 |

**24"**  
DEPTH

|     |             |
|-----|-------------|
| 24" | EXU242484V4 |
| 30" | EXU243084V4 |
| 36" | EXU243684V4 |
| 42" | EXU244284V4 |
| 48" | EXU244884V4 |
| 54" | EXU245484V4 |
| 60" | EXU246084V4 |
| 72" | EXU247284V4 |

|     |             |
|-----|-------------|
| 22" | EXA242484V4 |
| 28" | EXA243084V4 |
| 34" | EXA243684V4 |
| 40" | EXA244284V4 |
| 46" | EXA244884V4 |
| 52" | EXA245484V4 |
| 58" | EXA246084V4 |
| 70" | EXA247284V4 |



Color: Speckled Gray (480).

### V5

#### 5-Shelf Vented Units

Starter

Add-On



| LENGTH | CODE        |
|--------|-------------|
| 24"    | EXU182484V5 |
| 30"    | EXU183084V5 |
| 36"    | EXU183684V5 |
| 42"    | EXU184284V5 |
| 48"    | EXU184884V5 |
| 54"    | EXU185484V5 |
| 60"    | EXU186084V5 |
| 72"    | EXU187284V5 |

| LENGTH | CODE        |
|--------|-------------|
| 22"    | EXA182484V5 |
| 28"    | EXA183084V5 |
| 34"    | EXA183684V5 |
| 40"    | EXA184284V5 |
| 46"    | EXA184884V5 |
| 52"    | EXA185484V5 |
| 58"    | EXA186084V5 |
| 70"    | EXA187284V5 |

|     |             |
|-----|-------------|
| 24" | EXU212484V5 |
| 30" | EXU213084V5 |
| 36" | EXU213684V5 |
| 42" | EXU214284V5 |
| 48" | EXU214884V5 |
| 54" | EXU215484V5 |
| 60" | EXU216084V5 |
| 72" | EXU217284V5 |

|     |             |
|-----|-------------|
| 22" | EXA212484V5 |
| 28" | EXA213084V5 |
| 34" | EXA213684V5 |
| 40" | EXA214284V5 |
| 46" | EXA214884V5 |
| 52" | EXA215484V5 |
| 58" | EXA216084V5 |
| 70" | EXA217284V5 |

|     |             |
|-----|-------------|
| 24" | EXU242484V5 |
| 30" | EXU243084V5 |
| 36" | EXU243684V5 |
| 42" | EXU244284V5 |
| 48" | EXU244884V5 |
| 54" | EXU245484V5 |
| 60" | EXU246084V5 |
| 72" | EXU247284V5 |

|     |             |
|-----|-------------|
| 22" | EXA242484V5 |
| 28" | EXA243084V5 |
| 34" | EXA243684V5 |
| 40" | EXA244284V5 |
| 46" | EXA244884V5 |
| 52" | EXA245484V5 |
| 58" | EXA246084V5 |
| 70" | EXA247284V5 |

### Optional Accessories

- ☐ Corner Connector Sets
- ☐ Bottom Shelf Dunnage Stands (Low or Tall)
- ☐ Shelf Identification Tags
- ☐ Wall Fastener
- ☐ Floor Fastener
- ☐ Shelf Divider Panel
- ☐ Shelf Divider Bars (Straight or Angled)
- ☐ Single Shelf Sheet Pan Rack
- ☐ Single Shelf Security Cage
- ☐ Shelf Traverses (Single or Double)
- ☐ Drying and Storage Cradles
- ☐ Shelf Rails
- ☐ Universal Storage Rack
- ☐ Single and Add-on Can Racks

### Architect Specs

Posts and Traverses: Proprietary non-corrosive composite material.  
Post Connectors: Reinforced polypropylene.  
Shelf Plates: Reinforced polypropylene with Camguard® antimicrobial.  
Corner Connectors: Reinforced nylon.  
Adjustable Foot: Reinforced nylon.  
Traverse Dovetails: Reinforced nylon.  
Post Connector Collar Wedge: Reinforced nylon.

### Approvals



COMPONENT

Post Connectors, Corner Connectors, Floor Fastener, Wall Fastener, Identification Tags, Shelf Rails, Single Shelf Security Cage, Peg Board and Shelf Divider Bars are not NSF listed.

# CAMBRO®

www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.

Telephone: (714) 848-1555 Toll Free: (800) 854-7631 Customer Service: (800) 833-3003

© Cambro Manufacturing Company Huntington Beach, California 92647

Printed in U.S.A. 09/23

EXCS5

D082307