CAMBRO

Camshelving® Elements XTRA Series

Stationary Starter & Add-On Units
4 or 5 Solid Shelves

HEIGHT	DEPTHS	LENGTHS	
1	3	8	
84"	18"	24"	48"
	21"	30"	54"
	24"	36"	60"
		42"	72"

- **Starter Units include:**
  2 factory assembled post kits, 8 or 10 shelf traverses, traverse dovetails and shelf plates.
- **Add-On Units include:**
  1 factory assembled post kit, 8 or 10 shelf traverses, traverse dovetails and shelf plates.

All units ship complete in 1 box.

Store Safe
camguard
ANTIMICROBIAL SHELF PLATES

Project _____

Item No. _____

Model No. _____

Quantity _____

Stationary Starter Unit

Stationary Add-On Unit

Features & Benefits

- Designed to easily support the performance demands of a busy foodservice operation with medium to heavy storage needs.
- Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Withstands storage temperatures -36˚ to 190˚F (-38˚ to 88˚C). Impervious to moisture, chemicals, salt, food acids and humidity.
- Posts and traverses are made of a revolutionary, extremely strong composite material with a smooth, easy to clean surface. Stronger than common wire shelving and lighter in weight than Camshelving Premium Series. Traverse dovetails are separate from the posts and attach easily to secure the shelf traverses.
- Smooth polypropylene shelf plates contain Camguard, an antimicrobial technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation.
- Shelving Units interconnect in straight lines with shared posts. Uniquely engineered Post Connectors offer exceptional cross stabilization. Weight bearing is uncompromised and space is maximized. No add-on clips or "S" hooks required.
- Easily install heavy-duty Corner Connectors (front and back clasp design) to add shelves in corners or to install middle shelves between 2 units without any loss of weight bearing. Maximizes usable and easy to access storage space.
- Posts and traverses wipe clean. Traverses and shelf plates remove easily for cleaning.
- Shelf traverses can be removed and adjusted at 4" (10,2 cm) increments.
- Sturdy reinforced nylon foot adjusts easily to level units.
- Requires some assembly with minimal parts. Use a rubber mallet only.
- Lifetime warranty against rust and corrosion (posts, traverses and shelf plates).
- Available in 1 color – Speckled Gray (480).

WEIGHT BEARING CAPACITY

Weight must be evenly distributed across the entire shelf.

		UNIT LENGTH 24" – 60"	UNIT LENGTH 72"
SINGLE UNIT	Unit only	2400 lbs.	2400 lbs.
	Shelf only	800	600
	Unit with dunnage stand*	2800	2700
	Bottom shelf with dunnage stand*	1200	900

		UNIT LENGTH 24" – 60"	
CORNER UNIT With 2 Dunnage Stands required	Unit only	2400	—
	Shelf only	800	—
	Bottom shelf with dunnage stands*	1200	—

		UNIT LENGTH 24" – 60"	
INTERMEDIATE SHELVES Shelves Installed Between 2 Units	Unit only	2400	—
	Shelf only	800	—
	Bottom shelf with dunnage stands*	1200	—

*Dunnage Stands add stability and increase weight bearing capacity on bottom shelf only. Add to any shelf length. Highly recommended for Starter Units 54" (1375 mm) and longer, all Corner Units, U-Shape Units and units specified for heavier loads.

Approvals

NSF COMPONENT

Post Connectors, Corner Connectors, Floor Fastener, Wall Fastener, Identification Tags, Shelf Rails, Single Shelf Security Cage, Peg Board and Shelf Divider Bars are not NSF listed.

CAMBRO

www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.

Telephone: (714) 848-1555 **Toll Free:** (800) 854-7631 **Customer Service:** (800) 833-3003

© Cambro Manufacturing Company Huntington Beach, California 92647

Printed in U.S.A. 09/23

Camshelving® Elements XTRA Series

Stationary Starter & Add-On Units
4 or 5 Solid Shelves

Project _____

Item No. _____

Model No. _____

Quantity _____

S4
4-Shelf Solid Units

84" HEIGHT

Starter

Add-On



	LENGTH	CODE	LENGTH	CODE
18" DEPTH	24"	EXU182484S4	22"	EXA182484S4
	30"	EXU183084S4	28"	EXA183084S4
	36"	EXU183684S4	34"	EXA183684S4
	42"	EXU184284S4	40"	EXA184284S4
	48"	EXU184884S4	46"	EXA184884S4
	54"	EXU185484S4	52"	EXA185484S4
	60"	EXU186084S4	58"	EXA186084S4
	72"	EXU187284S4	70"	EXA187284S4
21" DEPTH	24"	EXU212484S4	22"	EXA212484S4
	30"	EXU213084S4	28"	EXA213084S4
	36"	EXU213684S4	34"	EXA213684S4
	42"	EXU214284S4	40"	EXA214284S4
	48"	EXU214884S4	46"	EXA214884S4
	54"	EXU215484S4	52"	EXA215484S4
	60"	EXU216084S4	58"	EXA216084S4
	72"	EXU217284S4	70"	EXA217284S4
24" DEPTH	24"	EXU242484S4	22"	EXA242484S4
	30"	EXU243084S4	28"	EXA243084S4
	36"	EXU243684S4	34"	EXA243684S4
	42"	EXU244284S4	40"	EXA244284S4
	48"	EXU244884S4	46"	EXA244884S4
	54"	EXU245484S4	52"	EXA245484S4
	60"	EXU246084S4	58"	EXA246084S4
	72"	EXU247284S4	70"	EXA247284S4

S5
5-Shelf Solid Units

Starter

Add-On



LENGTH	CODE	LENGTH	CODE
24"	EXU182484S5	22"	EXA182484S5
30"	EXU183084S5	28"	EXA183084S5
36"	EXU183684S5	34"	EXA183684S5
42"	EXU184284S5	40"	EXA184284S5
48"	EXU184884S5	46"	EXA184884S5
54"	EXU185484S5	52"	EXA185484S5
60"	EXU186084S5	58"	EXA186084S5
72"	EXU187284S5	70"	EXA187284S5
24"	EXU212484S5	22"	EXA212484S5
30"	EXU213084S5	28"	EXA213084S5
36"	EXU213684S5	34"	EXA213684S5
42"	EXU214284S5	40"	EXA214284S5
48"	EXU214884S5	46"	EXA214884S5
54"	EXU215484S5	52"	EXA215484S5
60"	EXU216084S5	58"	EXA216084S5
72"	EXU217284S5	70"	EXA217284S5
24"	EXU242484S5	22"	EXA242484S5
30"	EXU243084S5	28"	EXA243084S5
36"	EXU243684S5	34"	EXA243684S5
42"	EXU244284S5	40"	EXA244284S5
48"	EXU244884S5	46"	EXA244884S5
54"	EXU245484S5	52"	EXA245484S5
60"	EXU246084S5	58"	EXA246084S5
72"	EXU247284S5	70"	EXA247284S5

Color: Speckled Gray (480).

Optional Accessories

- ❑ Corner Connector Sets
- ❑ Bottom Shelf Dunnage Stands (Low or Tall)
- ❑ Shelf Identification Tags
- ❑ Wall Fastener
- ❑ Floor Fastener
- ❑ Shelf Divider Panel
- ❑ Shelf Divider Bars (Straight or Angled)
- ❑ Single Shelf Sheet Pan Rack
- ❑ Single Shelf Security Cage
- ❑ Shelf Traverses (Single or Double)
- ❑ Drying and Storage Cradles
- ❑ Shelf Rails
- ❑ Universal Storage Rack
- ❑ Single and Add-on Can Racks

Architect Specs

Posts and Traverses: Proprietary non-corrosive composite material.
Post Connectors: Reinforced polypropylene.
Shelf Plates: Reinforced polypropylene with Camguard® antimicrobial.
Corner Connectors: Reinforced nylon.
Adjustable Foot: Reinforced nylon.
Traverse Dovetails: Reinforced nylon.
Post Connector Collar Wedge: Reinforced nylon.

Approvals

NSF COMPONENT

Post Connectors, Corner Connectors, Floor Fastener, Wall Fastener, Identification Tags, Shelf Rails, Single Shelf Security Cage, Peg Board and Shelf Divider Bars are not NSF listed.

CAMBRO

www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.

Telephone: (714) 848-1555 **Toll Free:** (800) 854-7631 **Customer Service:** (800) 833-3003

© Cambro Manufacturing Company Huntington Beach, California 92647

Printed in U.S.A. 09/23