


OVEN RACKS ALUMINUM CONSTRUCTION

Channel's broad selection offers the best solutions for your applications.

LIFTER OPTIONS



/B Lift



**/C Lift
Specify:**

- 2 or 4 Lifters
- End and/or Side Placement



412A-OR/B



402A-OR

Custom Sizes Available

AVAILABLE ACCESSORIES

(visit www.channelmfg.com for complete list)

- /008 - X-bracing, Rear Mounted Pan Stop
- /009 - Pan Stop - Aluminum
- /011 - Caster Brakes (Set of 2)
- /2W - Double Welded Runners, Front & Back
- /A - Solid Top - Aluminum
- /B LIFT - Oven Rack Lifter
- /BA - Solid Bottom - Aluminum
- /C LIFT - Oven Rack Lifter
- /PP - Prison Package
- /S - Work Top - Stainless Steel
- /SW - Seal Weld (in lieu of plastic caps)
- ELC-69 - Cover — Bun Pan Racks 68" - 70" high

- Aluminum Bun Pan Oven Racks designed for high-temperature applications in rotating ovens and roll-in holding/proofing cabinets.
- Heavy-duty construction ensures durability and reliable performance in demanding commercial kitchens.
- Equipped with 4" phenolic plate casters that provide heat resistance and smooth mobility.
- Lifetime guarantee against rust.
- **CUSTOM SIZES AVAILABLE.** Contact Factory.

OVEN RACKS				STANDARD SERIES ALUMINUM CONSTRUCTION		NESTING ALUMINUM CONSTRUCTION	
Spacing/ Capacity	H	W	D	MODEL	WT	MODEL	WT
SINGLE SECTION							
EL 2" / 30	69¾"	20½"	26"	400A-OR-__	47	400AN-OR-__	47
EL 3" / 20	69¾"	20½"	26"	401A-OR-__	38	401AN-OR-__	38
EL 4" / 15	69¾"	20½"	26"	402A-OR-__	34	402AN-OR-__	34
EL 5" / 12	69¾"	20½"	26"	403A-OR-__	31	403AN-OR-__	31
EL 6" / 10	69¾"	20½"	26"	404A-OR-__	29	404AN-OR-__	29
SL 2" / 30	69¾"	28½"	18"	410A-OR-__	40	410AN-OR-__	40
SL 3" / 20	69¾"	28½"	18"	411A-OR-__	34	411AN-OR-__	34
SL 4" / 15	69¾"	28½"	18"	412A-OR-__	31	412AN-OR-__	31
SL 5" / 12	69¾"	28½"	18"	413A-OR-__	29	413AN-OR-__	29
SL 6" / 10	69¾"	28½"	18"	414A-OR-__	27	414AN-OR-__	27
DOUBLE SECTION							
SL 2" / 60	69¾"	29"	36"	410A-DOR-__	77	Nesting Oven Racks only available with /B Lift.	
SL 3" / 40	69¾"	29"	36"	411A-DOR-__	67		
SL 4" / 30	69¾"	29"	36"	412A-DOR-__	31		
SL 5" / 24	69¾"	29"	36"	413A-DOR-__	45		
SL 6" / 20	69¾"	29"	36"	414A-DOR-__	39		

Channel oven racks are equipped with 4" phenolic, high temperature casters with zerk grease fittings, 475°F continuous use, 575°F intermittent use. Use in Blast Chillers for freezing to -45°F



Project:	
Item:	
Quantity:	