



ELEVATION SERIES CUBE ICE MAKER

CIM2046/2047

Ice-O-Matic
Ice. Pure and Simple

Model:

- ☐ CIM2046
- ☐ CIM2047

CIM2046
ON B110



Features

- Space-saving 26.8" (681 mm) tall design.
- Produces up to 1,860 lbs (844 kg) of ice per day.
- *Harvest Assist* provides consistent ice production for the life of the ice maker while reducing energy consumption and increasing capacity.
- *Pure Ice*® exclusively by Ice-O-Matic. Built-in antimicrobial protection for the life of the ice maker inhibits bacteria growth on ice maker surfaces. Ice-O-Matic's optional water filtration system provides protection against unpleasant tastes, odors and scale formation.
- Durable, electroless nickel plating on all evaporator plates ensures reliability.
- *Longest warranty in the industry.* Purchase an Ice-O-Matic water filter with your cube ice maker, replace the filter every six months, and the evaporator warranty is extended to 7 years parts and labor (available in the U.S. and Canada only).
- Constructed from corrosion-resistant aluminum and fingerprint-proof plastic.



Safelce

*Available for factory or field install

Safelce Purification System is an add-on option for CIM machines that destroys Coronavirus, Flu, Odors, Mold and other biological contaminants, increasing the life of the machine by up to 30%.



<https://www.youtube.com/watch?v=toReJT8QG6A&t=7s>

Ice Form

FULL CUBE DIMENSIONS	
W x D x H (in.)	7 $\frac{1}{8}$ x 7 $\frac{1}{8}$ x 7 $\frac{1}{8}$
W x D x H (mm)	22 x 22 x 22
HALF CUBE DIMENSIONS	
W x D x H (in.)	3 $\frac{1}{8}$ x 7 $\frac{1}{8}$ x 7 $\frac{1}{8}$
W x D x H (mm)	10 x 22 x 22



CUBE

Bin Chart Kits for Combining Wider Bins with Smaller Models

ICE STORAGE BINS											
	Model No. Capacity Width	B25 242 lbs (110 kg) 30 in (762 mm)	B40 344 lbs (156 kg) 30 in (762 mm)	B42 351 lbs (160 kg) 22 in (559 mm)	B55 510 lbs (232 kg) 30 in (762 mm)	B700 680 lbs (308 kg) 30 in (762 mm)	B1000 1000 lbs (454 kg) 48 in (1,219 mm)	B110 854 lbs (388 kg) 48 in (1,219 mm)	B1300 1320 lbs (599 kg) 48 in (1,219 mm)	B1325 1325 lbs (601 kg) 60 in (1,524 mm)	B1600 1660 lbs (753 kg) 60 in (1,524 mm)
Kits											
	CIM2046	N/A						Kit Not Required			
	CIM2047	N/A						Kit Not Required			

*See Ice-O-Matic Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers.

Options & Accessories

WATER FILTERS		
Ice Machine Model	Manifold	
	System	Replacement
CIM2046	IFQ2-XL	IOMQXL (2)
CIM2047		

Note: All modular cube CIM units can be installed with manufacturer approved ozone delivery systems.

Ice Maker Warranty

COMMERCIAL WARRANTY	
Ice Maker	3 YEARS parts and labor
Evaporator and Compressor	5 YEARS parts
Evaporator (when enrolled in our filter program)	7 YEARS parts and labor

CIM2046/2047 CUBE ICE MAKER



ELEVATION SERIES CUBE ICE MAKER CIM2046/2047




CIM2046/2047 CUBE ICE MAKER

Water Cooled/Remote

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical junction box.
- E. Condenser water in, 3/8" FPT (water only).
- F. Condenser water out, 1/2" FPT (water only).

- G. Liquid line, 3/8" male quick connect coupling for precharged line set (remote only).
- H. Discharge line, 1/2" male quick connect coupling for precharged line set (remote only).
- I. Hole for remote electrical connections, 7/8" (remote only)



Operating Requirements

	MINIMUM	MAXIMUM
		60 Hz
Ambient Temp. Range Air	50°F (10°C)	100°F (38°C)
Water Temp.	40°F (4.4°C)	
Water Pressure	20 PSIG (1.4 BAR)	80 PSIG (5.5 BAR)
Remote Condenser Temp.	-20°F (-29°C)	120°F (50°C)

Dimensions

ALL MODELS	
W x D x H (in.)	48.25 x 24.25 x 26.8
W x D x H (mm)	1,226 x 616 x 660

Specifications

Model Number	Cond. Unit	Ice Production* per 24hrs		Water Usage gallons per 100 lbs of Ice 90°F air/70°F water		kWH Used per 100 lbs of ice @ 90°F air/ 70°F water	Voltage Characteristics	Min. Circuit Ampacity	Max Breaker Size	Approx. BTUs per hour
		70°F air/ 50°F water lbs (kg)	90°F air/ 70°F water lbs (kg)	Potable	Condenser					
CIM2046R**	Remote	1,830 (830)	1,533 (695)	14.9	N/A	4.5	208-230/60/1	25.6	40	27,500
CIM2046W	Water	1,860 (844)	1,639 (743)	14.8	150	3.9		24.1		
CIM2047R**	Remote	1,830 (830)	1,533 (695)	14.9	N/A	4.3	208-230/60/3	16.6	25	27,200
CIM2047W	Water	1,860 (844)	1,565 (709)	15.0	134.2	3.9		15.1		

* Daily ice production based on half cube configuration.

** Remote model CIM2046R and CIM2047R require the RC406C40 (replaces RCA3561) remote condenser.

Number of Wires: 3 (including ground)
Approx. Shipping Weight (lbs): CIM2046R 335 (152) • CIM2046W 335 (152) • CIM2047R 335 (152) • CIM2047W 335 (152)

REFRIGERANT: R404A