

# FF31L7FRTPC



26.13" x 17" x 22.38" (H x W x D)

Compact commercially approved front tap cold brew coffee dispenser in a classic white finish

### Highlights:

- Designed to serve cold brew coffee on tap
- Compact kegerator with front tap for easy and accessible dispensing
- ETL-S listed to ANSI-NSF Standard 7 for commercial use

### Product Features:

|                                            |                                                                                                                                            |
|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Compact Cold Brew Coffee Dispenser         | Kegerator features a pre-installed front tap accessed via the door, with all of the equipment needed to serve coffee from a 2.5 gallon keg |
| Commercially approved                      | ETL-S listed to ANSI-NSF Standard 7 for commercial use                                                                                     |
| Complete cold brew coffee tap kit included | Includes a nitrogen tank and regulator, tap draft arm, Sankey American tap, and the needed connection hardware                             |
| Commercial-grade equipment                 | The included tapping equipment is constructed from commercial-grade materials for added durability                                         |
| 2.5 gallon mini keg included               | Model is packaged with a refillable 2.5 gallon mini keg for easy service                                                                   |
| Stainless steel drip tray                  | Removable two-piece drip tray included for added convenience                                                                               |
| Accessible tap                             | Cold brew coffee tap is located on the front of the door, requiring no added reach                                                         |
| Lightweight design                         | Specifically designed for easier portability, opening up where unit can be placed                                                          |
| Factory-installed lock                     | Keyed lock allows you to secure the interior as needed, with a set of two keys included                                                    |

# FF31L7FRTPC Specifications:

| Overview                   |                   |
|----------------------------|-------------------|
| Height of Cabinet          | 26.13" (66 cm)    |
| Width                      | 17.0" (43 cm)     |
| Width with Door Open       | 17.75" (45 cm)    |
| Depth                      | 22.38" (57 cm)    |
| Depth with door at 90°     | 34.75" (88 cm)    |
| Capacity                   | 2.5 cu.ft. (71 L) |
| Defrost Type               | Automatic         |
| Door                       | White             |
| Cabinet                    | White             |
| US Electrical Safety       | ETL               |
| Canadian Electrical Safety | ETL-C             |
| Sanitation                 | ETL-S             |
| Amps                       | 1.3               |
| Voltage/Frequency          | 115 V AC/60 Hz    |
| Weight                     | 45.0 lbs. (20 kg) |
| Parts & Labor Warranty     | 1 Year            |
| Compressor Warranty        | 5 Years           |
| UPC                        | 761101158952      |
| Kegerator                  |                   |
| Door Swing                 | RHD               |
| Reversible                 | No                |
| Tap Kit                    | Yes               |
| Number of Taps             | 1                 |
| Adjustable Shelves         | Yes               |
| Shelf Type                 | Chrome            |
| Shelf Qty                  | 4                 |
| Thermostat Type            | Digital           |
| Interior Light             | Yes               |
| Refrigerant                | R600a             |
| Refrigerant Amount         | 0.06 oz.          |
| High Side PSI              | 270.0             |
| Low Side PSI               | 103.0             |
| Inter Height               | 21.25" (54 cm)    |
| Interior Width             | 13.5" (34 cm)     |
| Interior Depth             | 14.75" (37 cm)    |
| Compressor Step Height     | 7.5" (19 cm)      |
| Compressor Step Width      | 13.5" (34 cm)     |
| Compressor Step Depth      | 5.0" (13 cm)      |

|                   |              |
|-------------------|--------------|
| Temperature Range | 34°F to 43°F |
| Sound Level       | 34 dB        |

