

# SBC58BLBICSSADA



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap beer dispenser in stainless steel

**Highlights:**

32 inch height fits under lower ADA compliant counters

Commercially listed to NSF-7 standards

Complete stainless steel exterior finish for true luxury under the counter

**Product Features:**

|                        |                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------|
| ADA compliant height   | Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters          |
| Commercially approved  | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings               |
| Built-in capable       | Front-breathing design allows fully recessed installation under counters                                  |
| Complete tap kit       | Includes a 5 lb. CO2 tank and regulator, dual tap draft arm, Sankey American tap, and connection hardware |
| Dual tap system        | Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs                                     |
| Stainless steel finish | Door and cabinet are wrapped in 304 grade stainless steel for a professional look with lasting durability |
| Professional handle    | Curved towel bar style handle in brushed stainless steel                                                  |
| Adjustable thermostat  | Interior dial thermostat ensures easy temperature management                                              |
| Automatic defrost      | No-frost operation for minimum user maintenance                                                           |

### SBC58BLBICSSADA Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Nominal Height             | 32.0" (81 cm)      |
| Height of Cabinet          | 32.0" (81 cm)      |
| Height to Hinge Cap        | 32.25" (82 cm)     |
| Nominal Width              | 24.0" (61 cm)      |
| Width                      | 23.63" (60 cm)     |
| Nominal Depth              | 23.0" (58 cm)      |
| Depth                      | 22.75" (58 cm)     |
| Depth with Handle          | 24.75" (63 cm)     |
| Depth with door at 90°     | 45.0" (114 cm)     |
| Capacity                   | 5.5 cu.ft. (156 L) |
| Defrost Type               | Automatic          |
| Door                       | Stainless Steel    |
| Cabinet                    | Stainless Steel    |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Sanitation                 | ETL-S              |
| Amps                       | 1.2                |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 110.0 lbs. (50 kg) |
| Parts & Labor Warranty     | 1 Year             |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101069647       |
| Kegeerator                 |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Tap Kit                    | Yes                |
| Height with Tap            | 47.5" (121 cm)     |
| Number of Taps             | 2                  |
| Thermostat Type            | Dial               |
| Interior Light             | Yes                |
| Fan Type                   | Exterior           |
| Refrigerant                | R600a              |
| Refrigerant Amount         | 0.64 oz.           |
| High Side PSI              | 180.0              |
| Low Side PSI               | 80.0               |
| Inter Height               | 25.75" (65 cm)     |
| Interior Width             | 21.0" (53 cm)      |

|                        |                |
|------------------------|----------------|
| Interior Depth         | 17.75" (45 cm) |
| Compressor Step Height | 6.5" (17 cm)   |
| Compressor Step Width  | 21.0" (53 cm)  |
| Compressor Step Depth  | 5.5" (14 cm)   |
| Temperature Range      | 34° to 43°F    |

