

# Cayenne® Light Strips

## CAYENNE® LIGHT STRIPS ILLUMINATE FOOD SERVING DISPLAY AREAS OR FOOD PREPARATION AREAS.

- Structurally engineered aluminum housing offers maximum strength with minimal weight
- Standard polished stainless steel light reflector directs maximum light to the display area
- 120V, single-phase



### 40 WATT STANDARD BULBS



| LENGTH         | MODEL # | TOTAL NO. BULBS | AMP DRAW |
|----------------|---------|-----------------|----------|
| 18" (47.7 cm)  | 7286000 | 2               | 0.7      |
| 24" (60.9 cm)  | 7286100 | 2               | 0.7      |
| 30" (76.2 cm)  | 7286200 | 2               | 0.7      |
| 36" (91.4 cm)  | 7286300 | 4               | 1.4      |
| 42" (106.6 cm) | 7286400 | 4               | 1.4      |
| 48" (121.9 cm) | 7286500 | 4               | 1.4      |
| 54" (137.1 cm) | 7286600 | 6               | 2        |
| 60" (152.4 cm) | 7286700 | 6               | 2        |
| 66" (167.6 cm) | 7286800 | 6               | 2        |
| 72" (182.8 cm) | 7286900 | 6               | 2        |

### 60 WATT DISPLAY BULBS



| LENGTH         | MODEL # | TOTAL NO. BULBS | AMP DRAW |
|----------------|---------|-----------------|----------|
| 18" (47.7 cm)  | 7286002 | 2               | 1        |
| 24" (60.9 cm)  | 7286102 | 2               | 1        |
| 30" (76.2 cm)  | 7286202 | 2               | 1        |
| 36" (91.4 cm)  | 7286302 | 4               | 2        |
| 42" (106.6 cm) | 7286402 | 4               | 2        |
| 48" (121.9 cm) | 7286502 | 4               | 2        |
| 54" (137.1 cm) | 7286602 | 6               | 3        |
| 60" (152.4 cm) | 7286702 | 6               | 3        |
| 66" (167.6 cm) | 7286802 | 6               | 3        |
| 72" (182.8 cm) | 7286902 | 6               | 3        |

Note: All light strips are custom ordered and therefore cannot be canceled or returned per Vollrath Terms & Conditions

## Teflon® Coated Shatterproof Light Bulbs

- Replacement bulbs – item 23236, Case Lot 4



| UNIT LENGTH | NO. OF 40 WATT BULBS | TOTAL AMP (120V) |
|-------------|----------------------|------------------|
| 18"-30"     | 2                    | .7               |
| 36"-48"     | 4                    | 1.4              |
| 54"-72"     | 6                    | 2.1              |
| 84"         | 8                    | 2.8              |

## Kool-Touch® Black Trim



- Prevents burns from contact with side surface
- Enhances the visual appearance of the heat strips or light strips
- Field retrofitable

| TRIM LENGTH    | ITEM #  | CASE LOT | TRIM LENGTH    | ITEM #  | CASE LOT |
|----------------|---------|----------|----------------|---------|----------|
| 18" (47.7 cm)  | 1789718 | 2        | 48" (121.9 cm) | 1789748 | 2        |
| 24" (60.9 cm)  | 1789724 | 2        | 54" (137.1 cm) | 1789754 | 2        |
| 30" (76.2 cm)  | 1789730 | 2        | 60" (152.4 cm) | 1789760 | 2        |
| 36" (91.4 cm)  | 1789736 | 2        | 66" (167.6 cm) | 1789766 | 2        |
| 42" (106.6 cm) | 1789742 | 2        | 72" (182.8 cm) | 1789772 | 2        |

For lengths over 72" (182.8 cm), order trim in two pieces that equal the desired length  
Some field trimming required

## Cord and Plug Mounting Options



Stainless Steel C Legs



Stainless Steel T Legs

| LEG STYLE                                     | ITEM #  | FOR USE WITH         |
|-----------------------------------------------|---------|----------------------|
| C-Leg 13" (33.0 cm)                           | 4450613 | Medium Wattage Units |
| T-Leg, Adjustable 8" to 15" (22.8 to 38.1 cm) | 44504   | Medium Wattage Units |

Note: UL requires all cord and plug heat strips, from all manufacturers, to be mounted on legs. All heat strips are custom ordered and therefore cannot be canceled or returned per Vollrath Terms & Conditions.

## Hard Wired Mounting Options



Top Surface



Center

| BRACKET STYLE                 | ITEM #             | CASE LOT |
|-------------------------------|--------------------|----------|
| Top surface mount (2 per set) | 1" (2.54 cm) 44545 | 2        |
|                               | 2" (5.08 cm) 44546 | 2        |
| Center Mount                  | 1" (2.54 cm) 44140 | 1        |
|                               | 2" (5.08 cm) 44145 | 1        |

Double the recommended number of brackets for dual units

Center Mount brackets are suggested for units over 72" (182.8 cm) in length. They may be used alone or in combination with Top Surface Mount brackets.

Non-combustible surfaces may use 1" clearance. Combustible surfaces require 2" clearance.

### RECOMMENDED NUMBER OF CENTER MOUNT BRACKETS

| UNIT LENGTH      | # OF BRACKETS |
|------------------|---------------|
| 18" (45.7 cm)    | 2             |
| > 18" (45.7 cm)  | 3             |
| > 42" (106.7 cm) | 4             |
| > 60" (152.4 cm) | 5             |
| > 84" (213.4 cm) | 6             |