

# PLASTIC PANS



## Super Pan® High-Temperature Plastic Pans

- Temperature range is -40°F to 375°F (-40°C to 190.6°C)
- High-temperature resin
- Amber pans are translucent for content visibility
- For use in hot steam tables or microwaves
- Not recommended for use in ovens, combi-steamers, or convection ovens



| PAN SIZE AND DIMENSIONS                                                             |                                                     | AMBER<br>ITEM # | BLACK<br>ITEM # | DEPTH<br>IN (MM) | BRIMFUL<br>CAPACITY<br>QT (L) | PAN<br>CASE<br>LOT | AMBER<br>SOLID<br>COVER | AMBER<br>SLOTTED<br>COVER | AMBER<br>FALSE<br>BOTTOM | COVER<br>CASE<br>LOT |
|-------------------------------------------------------------------------------------|-----------------------------------------------------|-----------------|-----------------|------------------|-------------------------------|--------------------|-------------------------|---------------------------|--------------------------|----------------------|
|    | FULL-SIZE<br>20% X 12% in.<br>530 x 325 mm<br>¼     | 9002410         | 9002420         | 2½ (65)          | 8.8 (8.3)                     | 6                  | 33100                   | 34100                     | 23100                    | 6                    |
|                                                                                     |                                                     | 9004410         | 9004420         | 4 (100)          | 13.6 (12.9)                   | 6                  | 33100                   | 34100                     | 23100                    | 6                    |
|                                                                                     |                                                     | 9006410         | 9006420         | 6 (150)          | 20.2 (19.2)                   | 6                  | 33100                   | 34100                     | 23100                    | 6                    |
|                                                                                     |                                                     | 9008410         | —               | 8 (200)          | 26.5 (25.1)                   | 3                  | 33100                   | 34100                     | 23100                    | 6                    |
|   | HALF-SIZE<br>10% x 12% in.<br>265 x 325 mm<br>½     | 9022410         | 9022420         | 2½ (65)          | 3.9 (3.7)                     | 6                  | 33200                   | 34200                     | 23200                    | 6                    |
|                                                                                     |                                                     | 9024410         | 9024420         | 4 (100)          | 5.9 (5.6)                     | 6                  | 33200                   | 34200                     | 23200                    | 6                    |
|                                                                                     |                                                     | 9026410         | 9026420         | 6 (150)          | 8.6 (8.1)                     | 6                  | 33200                   | 34200                     | 23200                    | 6                    |
|                                                                                     |                                                     | 9028410         | —               | 8 (200)          | 11 (10.4)                     | 3                  | 33200                   | 34200                     | 23200                    | 6                    |
|  | HALF-LONG SIZE<br>20% x 6% in.<br>530 x 162 mm<br>¾ | 9052410         | 9052420         | 2½ (65)          | 3.8 (3.6)                     | 6                  | 33500                   | —                         | —                        | —                    |
|                                                                                     |                                                     | 9054410         | 9054420         | 4 (100)          | 5.7 (5.4)                     | 3                  | 33500                   | —                         | —                        | —                    |
|                                                                                     |                                                     |                 |                 |                  |                               |                    |                         |                           |                          |                      |
|  | THIRD-SIZE<br>6% x 12% in.<br>176 x 325 MM<br>⅓     | 9032410         | 9032420         | 2½ (65)          | 2.4 (2.3)                     | 6                  | 33300                   | 34300                     | 23300                    | 6                    |
|                                                                                     |                                                     | 9034410         | 9034420         | 4 (100)          | 3.6 (3.4)                     | 6                  | 33300                   | 34300                     | 23300                    | 6                    |
|                                                                                     |                                                     | 9036410         | 9036420         | 6 (150)          | 5.3 (5.1)                     | 6                  | 33300                   | 34300                     | 23300                    | 6                    |
|                                                                                     |                                                     | 9038410         | —               | 8 (200)          | 6.8 (6.5)                     | 3                  | 33300                   | 34300                     | 23300                    | 6                    |
|  | FOURTH-SIZE<br>6% x 10% in.<br>162 x 265 mm<br>¼    | 9042410         | 9042420         | 2½ (65)          | 1.8 (1.7)                     | 6                  | 33400                   | 34400                     | 23400                    | 6                    |
|                                                                                     |                                                     | 9044410         | 9044420         | 4 (100)          | 2.7 (2.5)                     | 6                  | 33400                   | 34400                     | 23400                    | 6                    |
|                                                                                     |                                                     | 9046410         | 9046420         | 6 (150)          | 3.8 (3.6)                     | 6                  | 33400                   | 34400                     | 23400                    | 6                    |
|                                                                                     |                                                     |                 |                 |                  |                               |                    |                         |                           |                          |                      |
|  | SIXTH-SIZE<br>6% x 6% in.<br>176 x 162 mm<br>⅙      | 9062410         | 9062420         | 2½ (65)          | 1.1 (1)                       | 6                  | 33600                   | 34600                     | 23600                    | 6                    |
|                                                                                     |                                                     | 9064410         | 9064420         | 4 (100)          | 1.6 (1.5)                     | 6                  | 33600                   | 34600                     | 23600                    | 6                    |
|                                                                                     |                                                     | 9066410         | 9066420         | 6 (150)          | 2.2 (2.1)                     | 6                  | 33600                   | 34600                     | 23600                    | 6                    |
|                                                                                     |                                                     |                 |                 |                  |                               |                    |                         |                           |                          |                      |
|  | NINTH-SIZE<br>6% x 4% in.<br>176 x 108 mm<br>⅑      | 9092410         | 9092420         | 2½ (65)          | 0.6 (0.6)                     | 6                  | 33900                   | —                         | —                        | 6                    |
|                                                                                     |                                                     | 9094410         | 9094420         | 4 (100)          | 0.9 (0.9)                     | 6                  | 33900                   | —                         | —                        | 6                    |
|                                                                                     |                                                     |                 |                 |                  |                               |                    |                         |                           |                          |                      |

For pan layouts, see page 94.

Specifications: Super Pan shall be constructed of polycarbonate (low temperature: -40°F to 210°F) or high-temperature resin (high temperature: -40°F to 375°F) material. Corner of top of flange shall be designed with built-in concave indentation for impact resistance. All depths shall have anti-jamming design to prevent pans from sticking together. Full, two-thirds, half, half-long, and third sizes shall have ramped sides for easy removal from wells. Reverse formed edge shall be flattened for consistent tangent to well opening and for hand comfort. Pans shall have an "all-natural-framing shoulder" around the interior body of the pan, accenting the food product and providing an appealing presentation. The low-temperature line is available in clear or black, and the high-temperature line is available in amber or black. Pan size and capacity to be marked on all pans. NSF® certified. Meets Gastronorm (EN 631-1) standard.