


ENDURANCE™ SERIES | 36" Open-Top Burners & Griddle Top



36" RANGE

2 OPEN-TOP BURNERS & 24" GRIDDLE RIGHT*

	Standard Base	Griddle Control	Gas Type	Total BTU/hr
	36S-2B24GN	Manual	Natural	135,000
	36S-2B24GTN	Thermostatic	Natural	135,000
	36S-2B24GP	Manual	Propane	130,000
	36S-2B24GTP	Thermostatic	Propane	130,000
Convection Base				
	36C-2B24GN	Manual	Natural	132,000
	36C-2B24GTN	Thermostatic	Natural	132,000
	36C-2B24GP	Manual	Propane	127,000
	36C-2B24GTP	Thermostatic	Propane	127,000
Refrigerated Base				
	36R-2B24GN	Manual	Natural	100,000
	36R-2B24GTN	Thermostatic	Natural	100,000
	36R-2B24GP	Manual	Propane	95,000
	36R-2B24GTP	Thermostatic	Propane	95,000

Oven accepts full-size sheet pans.

*Griddle can be moved to left position for upcharge.

Manual griddle controls allow user to adjust temperature by turning the knob to adjust flame. Thermostatic griddle controls allow user to set and maintain a specific temperature.

See page 21 for optional flame safety device for open-top burners.



36S-2B24GT
Shown on optional casters



36C-2B24GT
Shown on optional casters



36R-2B24GT
Shown on optional casters

Pictures shown are for illustration purpose only. Actual product may vary.