


## ENDURANCE™ SERIES | 72" Open-Top Burners & Griddle Top



### 72" RANGE WITH 2 OVENS

6 OPEN-TOP BURNERS & 36" GRIDDLE RIGHT\*

Standard Base / Standard Base		Griddle Control	Gas Type	Total BTU/hr
	72SS-6B36GN	Manual	Natural	310,000
	72SS-6B36GTN	Thermostatic	Natural	310,000
	72SS-6B36GP	Manual	Propane	295,000
	72SS-6B36GTP	Thermostatic	Propane	295,000
Standard Base / Convection Base				
	72SC-6B36GN	Manual	Natural	307,000
	72SC-6B36GTN	Thermostatic	Natural	307,000
	72SC-6B36GP	Manual	Propane	292,000
	72SC-6B36GTP	Thermostatic	Propane	292,000
Convection Base / Convection Base				
	72CC-6B36GN	Manual	Natural	304,000
	72CC-6B36GTN	Thermostatic	Natural	304,000
	72CC-6B36GP	Manual	Propane	289,000
	72CC-6B36GTP	Thermostatic	Propane	289,000
Refrigerated Base (Left placement only) / Standard Base				
	72RS-6B36GN	Manual	Natural	275,000
	72RS-6B36GTN	Thermostatic	Natural	275,000
	72RS-6B36GP	Manual	Propane	260,000
	72RS-6B36GTP	Thermostatic	Propane	260,000
Refrigerated Base (Left placement only) / Convection Base				
	72RC-6B36GN	Manual	Natural	272,000
	72RC-6B36GTN	Thermostatic	Natural	272,000
	72RC-6B36GP	Manual	Propane	257,000
	72RC-6B36GTP	Thermostatic	Propane	257,000

Oven accepts full-size sheet pans.

\*Griddles and convection ovens can be moved to left position for upcharge.

Manual griddle controls allow user to adjust temperature by turning the knob to adjust flame.

Thermostatic griddle controls allow user to set and maintain a specific temperature.

See page 21 for optional flame safety device for open-top burners.