

900RX & MSA SERIES | Heavy Duty Performance, Convenience and Reliability

STANDARD FEATURES:

- 27,000 BTUs per 12" section, U-shaped steel burners.
- 1" thick steel plate, 24" deep.
- Embedded mechanical snap-action thermostat provides accurate temperature control from 200–550°F (+/- 15°F to set point at idle).
- 1 supervised pilot safety valve for every 2 burners; valve will completely shut off gas to pilot and burners if pilot extinguishes or gas supply is interrupted.
- 4" heavy duty adjustable legs.
- Cool bull nose design keeps the front rail cool to the touch at all times.
- High-capacity 6-quart grease drawer—2 for 60" and 72" sizes.
- External gas regulator provided in packaging.
- 900RX & MSA models are Vulcan Manual Clamshell (VMCS) compatible.



936RX

Dual electric/manual ignition with front manifold shut off valve provides convenience to busy operators (900 Series)



MSA48

Manual ignition (MSA Series)

900RX GRIDDLES | DUAL ELECTRIC/MANUAL IGNITION

Model	Dimensions (W x D x H)	Cooking Height	Total BTU/hr.	No. of Drawers
924RX	24" x 31½" x 15¼"	11⅞"	54,000	1
936RX	36" x 31½" x 15¼"	11⅞"	81,000	1
948RX	48" x 31½" x 15¼"	11⅞"	108,000	1
960RX	60" x 31½" x 15¼"	11⅞"	135,000	2
972RX	72" x 31½" x 15¼"	11⅞"	162,000	2

Also available with a 30" deep steel plate.

MSA GRIDDLES | MANUAL IGNITION

Model	Dimensions (W x D x H)	Cooking Height	Total BTU/hr.	No. of Drawers
MSA24	24" x 31½" x 15¼"	11⅞"	54,000	1
MSA36	36" x 31½" x 15¼"	11⅞"	81,000	1
MSA48	48" x 31½" x 15¼"	11⅞"	108,000	1
MSA60	60" x 31½" x 15¼"	11⅞"	135,000	2
MSA72	72" x 31½" x 15¼"	11⅞"	162,000	2

Also available with exclusive Rapid Recovery™ composite griddle plate or a 30" deep steel plate.