

## GA SERIES / GA SERIES - POWERSTEAM™

### STANDARD FEATURES:

- Professional controls with 60-minute timer, buzzer and constant steam feature, cook/ready lights and power switch.
- Stainless steel exterior and cooking compartments with coved interior corners.
- Heavy duty door and latch mechanism.
- Long-life door gasket with exclusive Vulcan pan guard.
- Split water line connection.
- 115V cord and plug for control operation.

### GA SERIES | CABINET BASE - GAS

Model	Pan Capacity*	Input	Standard Power Supply
C24GA6	6	125,000 BTU/hr.	208V, 60 Hz, 3 Phase
C24GA10	10	125,000 BTU/hr.	208V, 60 Hz, 3 Phase

NOTE: Can be field converted to: 208V, 60-50 Hz, 1 Phase | 240V, 60-50 Hz, 3 Phase | 240V, 60-50 Hz, 1 Phase.

NOTE: Available with optional propane.

\*12" x 20" x 2½" Pan



**C24GA10**  
10-Pan Capacity

**Same standard features on GA Series, but with added superheated 235°F high-energy steam:**

### GA SERIES - POWERSTEAM™ TECHNOLOGY | CABINET BASE - GAS

Model	Pan Capacity*	Input	Standard Power Supply
C24GA6 PS	6	125,000 BTU/hr.	208V, 60 Hz, 3 Phase
C24GA10 PS	10	125,000 BTU/hr.	208V, 60 Hz, 3 Phase

NOTE: Can be field converted to: 208V, 60-50 Hz, 1 Phase | 240V, 60-50 Hz, 3 Phase | 240V, 60-50 Hz, 1 Phase.

NOTE: Available with optional propane.

\*12" x 20" x 2½" Pan



**C24GA10 PS**  
10-Pan Capacity

## FLOOR STEAMERS | *Field-Installed Accessories and Factory-Installed Options*

### FIELD-INSTALLED ACCESSORIES

#### HEAT SHIELD

Heat deflector for control side



**CSTMHTE SHIELD**  
*For all floor steamer models*

#### QUICK DISCONNECT HOSE

3/4" x 4' quick disconnect hose with restraining device



**3/4QD-HOSE-4**  
*For all gas steamers*

#### WATER FILTRATION



ScaleBlocker® Water Filtration System

**SMF620 SYSTEM**  
*For all floor steamer models*



ScaleBlocker® Kit includes cartridge & ScaleRelease™

**SMF620 PMKIT**  
*For SMF620 SYSTEM*



Flex S/S water connection 72", 3/4 GHT on both ends, per each, 2 required

**HOSEWTR 3/4BBV**  
*For SMF600 SYSTEM*

### FACTORY-INSTALLED OPTIONS

#### Electrical Options:

220V, 60 Hz, 1 Phase

**ET Base**

N/A

**PowerSteam™**

C24GA6 PS  
C24GA10 PS

**LWE**

N/A

**GA**

C24GA6  
C24GA10

480V, 60 Hz, 3 Phase

C24ET6  
C24ET10

C24ET6 PS  
C24ET10 PS

N/A

N/A

380V, 3 Phase

N/A

C24ET6 PS  
C24ET10 PS

N/A

N/A

415V, 3 Phase

N/A

C24ET6 PS  
C24ET10 PS

N/A

N/A

440V, 3 Phase

N/A

C24ET6 PS  
C24ET10 PS

N/A

N/A

#### Security Package:

##### C24CT-PPS

Security screws, tack welds and controls protected by lockable cover (lock by others)

C24ET6  
C24ET10

C24GA6 PS  
C24GA10 PS

C24ET6 LWE  
C24ET10 LWE

C24GA6  
C24GA10