








## K SERIES - TILTING COUNTER & FLOOR | OPTIONS & ACCESSORIES

### FIELD-INSTALLED ACCESSORIES

TILTING KETTLE STRAINERS	STANDS		COVERS
Strainer for tilting kettles	Stainless steel stand with flanged feet for electric kettle with sliding drain pan	Economy stand for electric kettle without sliding drain pan	Stainless steel lift-off cover with lid hanger
			
<b>STRAINR K6</b> <i>K6ETT</i> <b>STRAINR K12</b> <i>K12ETT</i> <b>STRAINR K20</b> <i>K20ETT</i>	<b>STAND VSKT30</b> <i>K6ETT, K12ETT</i>	<b>STAND VSKTEC</b> <i>K6ETT, K12ETT</i>	<b>COVER K6</b> <i>K6ETT</i> <b>COVER K12</b> <i>K12ETT</i> <b>COVER K20</b> <i>K20ETT</i>

Accessory Code	Description	Available on
CORDPLG 3PAN1P 	6' Cord and plug set rated to <b>45 Amps, 208-240V, 1 Phase</b> ; cable 8/3 90C UL*; angled plug HBL9462C NEMA 14-60P	K6ETT
CORDPLG 3PAN3P 	6' Cord and plug set rated to <b>40 Amps, 208-240V, 3 Phase</b> ; cable 8/4 90C UL*; angled plug HBL8462C NEMA 15-60P	K6ETT
CORDPLG 5PAN3P 	6' Cord and plug set rated to <b>55 Amps, 208-240V, 3 Phase</b> ; cable 6/4 90C UL*; angled plug HBL8462C NEMA 15-60P	K12ETT K20ETT
CORDPLG 5P480 	6' Cord and plug set rated to <b>30 Amps, 480V, 3 Phase</b> ; cable 8/4 90C UL*; straight plug HBL2731 NEMA L16-30P	K6ETT K12ETT, K20ETT

\*UL classification (SOW, SOOW, SEO and SEOW).

### FACTORY-INSTALLED OPTIONS

Code	Security Option:	Available on
KETT-PPS	Security fasteners and tack welds with controls protected by lockable cover (lock by others)	K6ETT, K12ETT, K20ETT
	<b>Electric Options:</b>	
	480V, 60 Hz, 3 Phase	K6ETT(7.5 kW), K12ETT(12 kW), K20ETT(12 kW)
	380V, 3 Phase	K6ETT, K12ETT, K20ETT
	415V, 3 Phase	K6ETT, K12ETT, K20ETT
	440V, 3 Phase	K6ETT, K12ETT, K20ETT

**VEKT SERIES | SPEC LINE TILTING KETTLE / TABLE COMBO****FIELD-INSTALLED ACCESSORIES****STRAINERS**

Strainer for tilting kettles



**STRAINR K6** (6-gallon)  
**STRAINR K12** (12-gallon)

**TABLES**

Table with sliding drain pan



**KT26 TABLE** (26")  
**KT50 TABLE** (50")  
**KT64 TABLE** (64")  
**KT80 TABLE** (80")

**COVERS**

Stainless steel lift-off cover with lid hanger



**COVER K6** (6-gallon)  
**COVER K12** (12-gallon)

**FACTORY-INSTALLED OPTION****Option**

480V, 60 Hz, 3 Phase (each kettle)

380V, 3 Phase

415V, 3 Phase

440V, 3 Phase

**Available on**

K6ETT, K12ETT

K6ETT, K12ETT

K6ETT, K12ETT

K6ETT, K12ETT