

Model 600CWP



Outdoor, Cold Wall, Slant Front, Double Solid Doors Ice Merchandiser

Model	Dimensions D x W x H	Volts / Hertz / Phase	Amps	Unit H.P.	Refrigerant	Capacity (Cu. Ft.)	Approx. Shipping Weight (lbs.)
600CWP	Ext. 35" x 70.25" x 72" Int. 31" x 66.25" x 53"	115V / 60HZ / 1PH	5.98 amps / 15-amp circuit	1/3	R-290	60	390

Agency Listings

- ETL Listed in accordance to UL 60335-1-89 and UL 60335-2-89 Standard - 2nd Edition

Connections

- Electrical connection: Heavy Duty 12-Gauge 10-Foot. Cord with plug
- Condensation Plumbing Connection: N/A

Optional Features

- Bright Aluminum Diamond Plate Kick Plate
- Door Opening Ice Breaker Bar
- 4" Casters with 1/4 " Aluminum Angle Perimeter Frame
- TX Valve Metering Device
- ETL Listed in accordance to NSF7 Standard

Standard Features

- Merchandiser designed to hold product between 10°F to 20°F
- 26-gauge Ceram-A-Star pre-painted steel exterior/26-gauge galvanized steel interior
- Solid Insulated Door with TPE Magnetic, Positive Seal, Self-Closing Gasket
- Top Mounted Refrigeration System with Low Global Warming Potential
- Copper Tube In Wall Evaporator with Capillary Tube - Cold Wall (CW)
- Environmentally-friendly, nonflammable, foamed-in-place insulation that provides exceptional energy efficiency.
- Electronic Control System Gives Service Friendly Fault Codes
- Floor Racks
- Solid Injection Molded Feet