

Model 630CWP



Single Door, Upright, Outdoor Ice Merchandiser

Model	Dimensions D x W x H	Volts / Hertz / Phase	Amps	Unit H.P.	Refrigerant	Capacity (Cu. Ft.)	Approx. Shipping Weight (lbs.)
630CWP	Ext. 35" x 62" x 79" Int. 31" x 58" x 59"	115V / 60HZ / 1PH	5.8 amps / 15- amp circuit	1/3	R-290	61	395

Agency Listings

- ETL Listed in accordance to UL 60335-1-89 and UL 60335-2-89 Standard - 2nd Edition

Connections

- Electrical connection: Heavy Duty 12-Gauge 10-Foot. Cord with plug

Optional Features

- 24" LED Light
- Bright Aluminum Diamond Plate Kick Plate
- Door Opening Ice Breaker Bar
- 4" Casters with 1/4 " Aluminum Angle Perimeter Frame
- TX Valve Metering Device
- ETL Listed in accordance to NSF7 Standard
- Shelves

Standard Features

- Merchandiser designed to hold product between 10°F to 20°F
- 26-gauge Ceram-A-Star pre-painted steel exterior/26-gauge galvanized steel interior
- Solid Insulated Door with TPE Magnetic, Positive Seal, Self-Closing Gasket
- Top Mounted Refrigeration System with Low Global Warming Potential
- Copper Tube in Wall Evaporator with Capillary Tube (Cold Wall)
- Environmentally-friendly, nonflammable, foamed-in-place insulation that provides exceptional energy efficiency.
- Electronic Control System Gives Service Friendly Fault Codes
- Floor Racks
- Solid Injection Molded Feet