

Chest Freezer Solid Top Chest Freezer 38 " Long

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



738089 (KCCF073WS)

Solid Top Chest Freezer 38
" Long

Short Form Specification

Item No.

Solid top chest freezer with foamed lid and soft closing mechanism to ensure gentle lid closure. Internal and external structure in white painted steel. Basket, vertical basket divider, NSF thermometer and lock included as standard. Defrost water drain with plug for easy cleaning. R600a refrigerant gas for the lowest environmental impact (GWP=3). The temperature range is -15° to 10°F. ETL safety and sanitation listed for US and Canada. Equipped with NEMA 5-15P plug.

Main Features

- Basket - Durable and reliable for safety in food storage (1 basket included).
- NSF®-Certified Temperature Gauge - Durable and reliable for safety in food storage.
- Heavy-Duty, Locking Casters - Keeps unit in place but allows position adjusting.
- Low energy consumption

Construction

- Static Condenser
- Mechanical Control panel with adjustable temperature
- Internal Temperature Display
- Freezer Basket
- Foamed Lid for best insulation and product robustness
- Locking Lids & Key Protect the contents of the unit
- Exterior Finish: Textured Painted Steel
- Interior Finish: Painted Steel

Sustainability


- CFC and HCFC free (ecological refrigerant type: R600a).
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.

Optional Accessories


- Basket for Solid Top 7 cu.ft. Chest Freezer 16.26x8.66x16.85 in (413x220x428 mm) PNC 882002 ☐

APPROVAL: _____

Front



Side



El = Electrical connection

Electric

Supply voltage:	115 V/1 ph/60 Hz
Electrical power, max:	0.13 kW
Plug type:	USA NEMA 5-15P

Capacity:

Gross capacity:	16.1 cu.feet
-----------------	--------------

Key Information:

Internal Dimensions (width):	27 1/4" / (692 mm)
External dimensions, Width:	37 13/16" (960 mm)
External dimensions, Depth:	22 1/8" (562 mm)
External dimensions, Height:	32 11/16" (830 mm)
Internal Dimensions (depth):	14 7/8" / (378 mm)
Internal Dimensions (width):	32 1/16" / (814 mm)
Net weight:	60 lbs (27.27 kg)
Shipping width:	23 1/32" (585 mm)
Shipping height:	34 5/8" (880 mm)
Shipping weight:	99 lbs (45 kg)
Shipping volume:	18.27 ft ³ (0.52 m ³)
Approvals	ETL C&US;ETL SANITATION

Refrigeration Data

Operating temperature min.:	-22 °F
Compressor power:	1/8 hp
Operating temperature max.:	3.2 °F

Sustainability

Current consumption:	1.2 Amps
Refrigerant type:	R600a
GWP Index:	3
Refrigerant weight:	45 g

