

FOCUS

FOODSERVICE, LLC

Item # _____

Job _____



FOCUS SHELIVING

Black Epoxy Coated Wire Shelving

The black color provides an excellent complement to any décor and creates an effective vehicle for displaying product.

- **Design:** The open wire design of these heavy gauge black epoxy coated shelves minimizes dust accumulation and allows a free circulation of air; greater visibility of stored items and greater light penetration.
- **Versatile:** FOCUS SHELIVING can change as quickly as your needs change. By using various sizes, hundreds of shelving configurations become possible.
- **Fast and Secure Assembly:** Posts with the double groove visual guide feature, have circular grooves at 1" (25mm) intervals. A tapered split sleeve (plastic) snaps together around each post. Tapered openings in the shelf corners slide over the tapered split sleeves to lock on the shelf. Shelf is assembled in minutes without the use of any special tools.
- **Shelf Ribs:** Run front to back, allowing you to slide items on and off shelves smoothly.
- **Shelf Accessibility:** Shelves can be adjusted at 1" (25mm) intervals along the entire length of the post.
- **Durable:** FOCUS black epoxy coated shelving is rugged, standing up to years of heavy use.
- **Adjustable Feet:** Bolt levelers compensate for uneven surfaces.
- **Strength:** Each shelf up to 48" in length is rated to support up to 800 lbs. of uniformly distributed weight. Shelves longer than 48" support 600 lbs.

FOCUS BLACK EPOXY COATED WIRE SHELIVING

FOCUS BLACK EPOXY COATED WIRE SHELVING

Job _____

Wire Shelves



Split Sleeves



"S" Hooks

Used to "add-on" shelving units with only two posts required.
Item No. 93333BK Black Epoxy



Posts

Posts are grooved at 1" (25mm) increments and numbered at 2" (50mm) increments. Posts are double grooved every 8" (203mm) for easy identification.



Width		Length		Approx. Pkd. Wt.		Item No. Black Epoxy
(in)	(mm)	(in)	(mm)	(lbs.)	(kg)	
14	355	24	610	6	2.7	FF1424BK
14	355	30	760	7	3.2	FF1430BK
14	355	36	910	8	3.6	FF1436BK
14	355	42	1060	9.5	4.3	FF1442BK
14	355	48	1220	10.5	4.7	FF1448BK
14	355	60	1525	14	6.3	FF1460BK
14	355	72	1825	17	7.7	FF1472BK
18	455	24	610	7	3.2	FF1824BK
18	455	30	760	8	3.6	FF1830BK
18	455	36	910	9.5	4.3	FF1836BK
18	455	42	1060	11	5.0	FF1842BK
18	455	48	1220	12	5.4	FF1848BK
18	455	54	1370	14.5	6.6	FF1854BK
18	455	60	1525	17	7.7	FF1860BK
18	455	72	1825	20	9.1	FF1872BK
21	530	24	610	8	3.6	FF2124BK
21	530	30	760	9	4.1	FF2130BK
21	530	36	910	11	5.0	FF2136BK
21	530	42	1060	12	5.4	FF2142BK
21	530	48	1220	14	6.4	FF2148BK
21	530	54	1370	16	7.6	FF2154BK
21	530	60	1525	18	8.2	FF2160BK
21	530	72	1825	24	10.9	FF2172BK
24	610	24	610	9	4.1	FF2424BK
24	610	30	760	11	5.0	FF2430BK
24	610	36	910	13	5.9	FF2436BK
24	610	48	1220	16	7.3	FF2448BK
24	610	54	1370	18	8.6	FF2454BK
24	610	60	1525	21	9.5	FF2460BK
24	610	72	1825	26	11.8	FF2472BK

Height		Approx. Pkd. Wt.		Item No. Stationary	Item No. Mobile
(in.)	(mm)	(lbs.)	(kg)		
7	190	0.5	0.2	FG007BK	FGN007BK
15	381	1	0.5	FG015BK	FGN015BK
33	876	2	0.9	FG033BK	FGN033BK
54	1386	3	1.4	FG054BK	FGN054BK
63	1589	3.5	1.6	FG063BK	FGN063BK
74	1895	4	1.8	FG074BK	FGN074BK
86	2200	5	2.3	FG086BK	FGN086BK