

VACUUM SINGLE CHAMBER


Models | 450A | 450T | 550A | 560A | 580A




MODELS 450A, 550A, 560A AND 580A

		450A	550A	560A	580A
SEAL BARS	Length	A 19.1" (485 mm)	26" (660 mm)	26" (660 mm)	33.5" (855 mm)
	Qty	2	2	2	2
	Distance between	B 23" (584 mm)	23.25" (591 mm)	31" (787 mm)	36.75" (933 mm)
CHAMBER DIMENSIONS	Height	9.5" (241 mm)	8" (203 mm)	8" (203 mm)	8" (203 mm)
BUSCH PUMP	Std.	40 m ³ /h	63 m ³ /h	100 m ³ /h	200 m ³ /h
	Width	E 30.5" (775 mm)	31" (787 mm)	38" (965 mm)	45.25" (1,153 mm)
MACHINE DIMENSIONS	Depth	F 32" (813 mm)	36" (914 mm)	36" (914 mm)	46.5" (1,183 mm)
	Height	G 44" (1,118 mm)	47" (1,194 mm)	47" (1,194 mm)	43.75" (1,113 mm)
	POWER SUPPLY	208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz
MICROPROCESSOR		MC-40	MC-40	MC-40	MC-40

2 SEAL BARS



MC-40



BASIC FEATURES

- Single chamber
- Stainless steel construction
- Twin seal element – Double seam band
- Vacuum sensor - Vacuum level controlled in percentage, directly with Microprocessor
- Filler plates
- Cover latch
- Wheels (stainless steel)
- Rear panel
- Crate
- Certification: ETL listed C & US (CSA & UL)

OPTIONAL FEATURES

- Electric cut-off - Two wire seal system: outside wire cuts off excessive part of bag
- Bi-active seal - Sealing from top and bottom for thick pouches and aluminum bags on models 550A, 560A and 580A
- Modified atmosphere packaging (MAP) - Increases the product's shelf life, provides extra protection, prevents colouring
- Air regulator – Regulates air pressure in the seal bars bladders with compressed air (not included)
- Adjustable venting system - Controlled decompression of the vacuum chamber
- 12" (305 mm) chamber lid on models 550A, 560A and 580A
- Vacuum pump sizes
- Stainless steel tilted insert for liquid products
- Silencer
- Other voltages available
- Heated control box for microprocessor
- Service kit for standard maintenance

All features are subject to change without notice.