AGM / ASA SERIES

Heavy duty performance, convenience and reliability.

STANDARD FEATURES:

- 27,000 BTUs per 12" section, U-shaped steel burners
- 1" thick steel plate, 24" deep
- Manual controls are designed for high-heat operations
- 4" heavy duty adjustable legs
- High-capacity 6-quart grease drawer—2 for 60" and 72" sizes



AGM48

AGM SERIES GRIDDLES | MANUAL CONTROLS

Model	Dimensions (W x D x H)	Cooking Height	Total BTU/hr	No. of Drawers
AGM24	24" x 31½" x 15¼"	111/8"	54,000	1
AGM36	36" x 31½" x 15¼"	111/8"	81,000	1
AGM48	48" x 31½" x 15¼"	111/8"	108,000	1
AGM60	60" x 31½" x 15¼"	111/8"	135,000	2
AGM72	72" x 31½" x 15¼"	111/8"	162,000	2

ALL STANDARD FEATURES FROM AGM SERIES, PLUS THE FOLLOWING:

- 1" thick steel plate, 24" deep (also available in 30" deep—contact factory)
- Embedded mechanical snap-action thermostat provides accurate temperature control from 200– 550°F (+/- 15°F to set point at idle)
- 1 supervised pilot safety valve for every 2 burners; valve will completely shut off gas to pilot and burners if pilot extinguishes or gas supply is interrupted)
- Cool bull nose design keeps the front rail cool to the touch at all times

- · External gas regulator provided in packaging
- · Manual ignition



ASA SERIES GRIDDLES | SNAP-ACTION THERMOSTAT

Model	Dimensions (W x D x H)	Cooking Height	Total BTU/hr	No. of Drawers
ASA24	24" x 31½" x 15¼"	111/8"	54,000	1
ASA36	36" x 31½" x 15¼"	111/8"	81,000	1
ASA48	48" x 31½" x 15¼"	111/8"	108,000	1
ASA60	60" x 31½" x 15¼"	111/8"	135,000	2
ASA72	72" x 31½" x 15¼"	111/8"	162,000	2