

## **SAFE FEATURES**

## BODY & DOOR

- · All steel construction
- 1 hour 350°F fire rating [Tested in temperatures up to 1750°F]
- Body has an overall thickness of 1¾" consisting of a steel plate lined with fire-resistant material
- Door has an overall thickness of 51/8" lined with fire-resistant material
- 2 story impact rating
- Massive 1½" diameter solid steel locking bolts & deadbolts
- · Heavy-duty solid steel hinges
- 3-way locking system
- Heat activated seal
- Fully upholstered interior
- Fully adjustable shelving system
- Interior outlet with 3 sockets & 2 USB ports
- Decorative brass spoke handle
- 4 pre-drilled anchor holes [Anchor kit included]

## LOCK Electronic

- Battery operated electronic lock [9V Battery required; not included]
- Lock protected by a drill resistant hard plate & punch-activated relocking system
- Multiple invalid code defense feature
- 2 user codes available
- Easily change your personal code
- Override key system [2 Keys included]

## Combination

- U.L. Listed Group II Combination Spy-Proof Lock
- Lock protected by a drill resistant hard plate & punch-activated relocking system



MBF**5922**E







MBF**7236**E

MODEL	EXTERIOR [HWD]	INTERIOR [HWD]	INTERIOR [CU.FT.]	SHELVING [NO.]	WEIGHT
MBF <b>5922</b>	59" × 22" × 20"	55¾" x 18¼" x 13"	7.6	HALF: 3 FULL: 1	484 lbs
MBF <b>6032</b>	59" × 32" × 22"	55¾" × 28½" × 15¼"	13.9	HALF: 3 FULL: 1	665 lbs
MBF <b>7236</b>	71" × 36" × 24"	67" x 32 ¼" x 16 %"	21.1	HALF:6 FULL:2	865 lbs

