



Model: _____ Item #: _____ Date: _____

Project: _____ Qty: _____ Approved By: _____

Front Door Mug Frosters

Refrigeration



FMC24-SS-R



Standard Features

- Fits (90) 10 oz. mugs
- Automatic defrost timer every 4 hours (push button manual mode also available)
- Two layers of shelving with floor rack
- Digital thermostat on front grille
- Heavy duty doors with stainless steel handle with built-in lock
- Eco-friendly refrigerant and insulation
- Pre-drilled bottom for optional casters (uses 1/4-20 self tapping 1/2"L screw)
- 5-Year Compressor Warranty
- 1-Year Parts & Labor Warranty

Model	Length	Height	Depth	Door Finish	Top Finish	Door Hinge	Weight
FMC24-BN-L	24"	35"	24"	Black Vinyl	Unfinished Top	Left	220 lbs.
FMC24-BN-R	24"	35"	24"	Black Vinyl	Unfinished Top	Right	220 lbs.
FMC24-BS-L	24"	36"	24"	Black Vinyl	1" Stainless Steel Top	Left	244 lbs.
FMC24-BS-R	24"	36"	24"	Black Vinyl	1" Stainless Steel Top	Right	244 lbs.
FMC24-SN-L	24"	35"	24"	Stainless Steel	Unfinished Top	Left	220 lbs.
FMC24-SN-R	24"	35"	24"	Stainless Steel	Unfinished Top	Right	220 lbs.
FMC24-SS-L	24"	36"	24"	Stainless Steel	1" Stainless Steel Top	Left	244 lbs.
FMC24-SS-R	24"	36"	24"	Stainless Steel	1" Stainless Steel Top	Right	244 lbs.

Specifications

Electrical	▪ 115V, 1 Phase, 60 Hz
	▪ Furnished with 8 ft. plug-in cord, which exists left or right rear of cooler
	▪ NEMA 5-15P plug configuration
	▪ Dedicated 15 Amp circuit recommended
Refrigeration	▪ R290 Hydrocarbon Refrigerant
	▪ 12°F - 17°F operating range
Plumbing	▪ Floor drain connects to condensate evaporator pan. No drain required.
Insulation	▪ 2" thick foamed-in-place polyurethane
Interior	▪ 20 gauge stainless steel walls with coved corners
	▪ Standard door opening: 19-3/4"W x 24-3/4"H
Doors	▪ 24"W doors
	▪ Black vinyl or stainless steel door finish
	▪ Stainless steel handles with built-in locks

