



SCAN TO
LEARN MORE

FOLLOW US:
f t i in d
krowne.com



HydroSift™

by Krowne



KR-HS2-KIT
SHOWN

FLAWLESS. FILTERED. FRESH.

Krowne's HydroSift™ Water Filters are the premier food-service water filtration solution. Our bacteriostatic filters diminishes limescale, reduces chlorine/chloramine, and eliminates bad tastes and odor. The result is clean, safe, and great tasting water ready to serve to your customers.

- ▶ Works with a variety of applications including, but not limited to: ice machines, slushie machines, countertop steamers, coffee or beverage dispensers, soda machines, combi ovens, steam ovens, & other high flow applications.
- ▶ Max flow rate varies depending on model:
2.5 GPM (KR-HSA, KR-HS1-KIT, and KR-HS2-KIT)
8.0 GPM (KR-HS3-KIT)
- ▶ Gallon capacity varies depending on model:
10,000 (KR-HSA, and KR-HS1-KIT)
15,000 (KR-HS2-KIT)
20,000 (KR-HS3-KIT)
- ▶ 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- ▶ 35° - 160°F operating temperature

Filter Assemblies

KR-HS1-KIT	Single Filter Assembly Kit
KR-HS2-KIT	Twin Filter Assembly Kit
KR-HS3-KIT	Triple Filter Assembly Kit
KR-HSA	Single Assembly with Filter Cartridge

Cartridges

KR-FC	Filter Cartridge
KR-SF	Sediment Filter Cartridge

Replacement Parts

23-200	3/4" PVC Ball Valve, NPT Male-Female
23-201	3/4" NPT Female Tee Fitting
23-202	3/4" x 1/4" Reducing Bushing
23-203	Pressure Gauge
23-204	3/4" x 3/4" Male to Male Nipple Fitting



Krowne
100 Haul Rd. • Wayne, NJ 07470
P: (800) 631-0442 • F: (973) 872-1129
sales@krowne.com • krowne.com



SCAN TO
LEARN MORE

FOLLOW US:
f t i in d
krowne.com



Single Water Filter Assembly Kit

KR-HS1-KIT

- 10,000 gallon capacity
- 2.5 GPM max flow rate
- 3/4" NPT water in and out connections
- 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- 35° - 160°F operating temp



Twin Water Filter Assembly Kit

KR-HS2-KIT

- 15,000 gallon capacity
- 2.5 GPM max flow rate
- 3/4" NPT water in and out connections
- 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- 35° - 160°F operating temp



Triple Water Filter Assembly Kit

KR-HS3-KIT

- 20,000 gallon capacity
- 8.0 GPM max flow rate
- 3/4" NPT water in and out connections
- 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- 35° - 160°F operating temp



Single Assembly with Filter Cartridge

KR-HSA

- 10,000 gallon capacity
- 2.5 GPM max flow rate
- 3/4" NPT water in and out connections
- 20-100 PSI non-shock working pressure (1.38-6.89 bar)
- 35° - 160°F operating temp



Filter Cartridge

KR-FC

- Bacteriostatic filter
- Diminishes limescale, reduces chlorine chloramine, and eliminates bad taste and odor
- For use in single, twin, and triple filter assemblies



Sediment Filter Cartridge

KR-SF

- Reduces sediment and silk
- For use in twin and triple filter assemblies



Krowne
100 Haul Rd. • Wayne, NJ 07470
P: (800) 631-0442 • F: (973) 872-1129
sales@krowne.com • krowne.com

