



Model: \_\_\_\_\_ Item #: \_\_\_\_\_ Date: \_\_\_\_\_  
Project: \_\_\_\_\_ Qty: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Gas Connector Kit 2

## Gas Connectors



### Standard Features

- For use with stationary and caster-mounted commercial kitchen equipment
- Male NPT End fittings rotate 360
- Heavy duty stainless steel corrugated tubing for flexibility
- Heavy duty stainless steel radial wrap prevents hose from stretching
- PVC Protective coating with anti-microbial agent for easy cleaning
- Welded construction for added durability
- For Indoor Use Only

### Specifications

|              |                               |
|--------------|-------------------------------|
| Pressure     | ▪ 1/2 psi                     |
| End Fittings | ▪ Carbon Steel, Chrome Plated |
| Tubing       | ▪ Stainless Steel 304         |
| Braiding     | ▪ Stainless Steel 304         |

### Includes:

| No. | Name                  | Description                                                                 |
|-----|-----------------------|-----------------------------------------------------------------------------|
| 1   | Gas Connector         | For stationary and caster-mounted kitchen equipment.                        |
| 2   | Quick Disconnect      | Easily disconnects gas hose to move equipment for maintenance and cleaning. |
| 3   | Restraining Cable Kit | Prevents hose from being pulled too far. Includes mounting hardware.        |

Visit [krowne.com](http://krowne.com) for complete replacement parts.

### Product Compliance

- ANSI Z21.41-2014 • CSA 6.9-2014 Quick Disconnect Devices For Use With Gas Fuel Appliances
- ANSI Z21.69-2009 • CSA 6.16-2009 Connectors For Moveable Gas Appliances
- ANSI Z21.69a-2012 • CSA 6.16a-2012 Addenda

| Model No. | Interior Size | Length | BTU/hr |
|-----------|---------------|--------|--------|
| M5024K2   | 1/2"          | 24"    | 87K    |
| M5036K2   | 1/2"          | 36"    | 77K    |
| M5048K2   | 1/2"          | 48"    | 68K    |
| M5060K2   | 1/2"          | 60"    | 60K    |
| M5072K2   | 1/2"          | 72"    | 55K    |
| M7524K2   | 3/4"          | 24"    | 232K   |
| M7536K2   | 3/4"          | 36"    | 218K   |
| M7548K2   | 3/4"          | 48"    | 180K   |
| M7560K2   | 3/4"          | 60"    | 158K   |
| M7572K2   | 3/4"          | 72"    | 139K   |
| M10024K2  | 1"            | 24"    | 414K   |
| M10036K2  | 1"            | 36"    | 379K   |
| M10048K2  | 1"            | 48"    | 334K   |
| M10060K2  | 1"            | 60"    | 294K   |
| M10072K2  | 1"            | 72"    | 279K   |
| M12524K2  | 1-1/4"        | 24"    | 699K   |
| M12536K2  | 1-1/4"        | 36"    | 615K   |
| M12548K2  | 1-1/4"        | 48"    | 541K   |
| M12560K2  | 1-1/4"        | 60"    | 476K   |
| M12572K2  | 1-1/4"        | 72"    | 419K   |

**WARNING:** Restraining Kits are required by law for all moveable gas equipment  
California Proposition 65 Warning

