Model: _____ Item #: _____ Date: _____

Project: _____ Qty: _____ Approved By: _____

Gas Connector Hose Only

Gas Connectors



Standard Features

- For use with stationary and caster-mounted commercial kitchen equipment
- Male NPT End fittings rotate 360°
- Heavy duty stainless steel corrugated tubing for flexibility
- Heavy duty stainless steel radial wrap prevents hose from stretching
- PVC Protective coating with anti-microbial agent for easy cleaning
- Welded construction for added durability
- For Indoor Use Only

Specifications

Pressure	▪ 1/2 psi
End Fittings	▪ Carbon Steel, Chrome Plated
Tubing	▪ Stainless Steel 304
Braiding	▪ Stainless Steel 304

Includes:

No.	Name	Description
1	Gas Connector	For stationary and caster-mounted kitchen equipment.

Visit krowne.com for complete replacement parts.

Product Compliance

- ANSI Z21.41-2014 • CSA 6.9-2014 Quick Disconnect Devices For Use With Gas Fuel Appliances
- ANSI Z21.69-2009 • CSA 6.16-2009 Connectors For Moveable Gas Appliances
- ANSI Z21.69a-2012 • CSA 6.16a-2012 Addenda

Model No.	Interior Size	Length	BTU/hr
M5024	1/2”	24”	87K
M5036	1/2”	36”	77K
M5048	1/2”	48”	68K
M5060	1/2”	60”	60K
M5072	1/2”	72”	55K
M7524	3/4”	24”	232K
M7536	3/4”	36”	218K
M7548	3/4”	48”	180K
M7560	3/4”	60”	158K
M7572	3/4”	72”	139K
M10024	1”	24”	414K
M10036	1”	36”	379K
M10048	1”	48”	334K
M10060	1”	60”	294K
M10072	1”	72”	279K
M12524	1-1/4”	24”	699K
M12536	1-1/4”	36”	615K
M12548	1-1/4”	48”	541K
M12560	1-1/4”	60”	476K
M12572	1-1/4”	72”	419K

WARNING: Restraining Kits are required by law for all moveable gas equipment
California Proposition 65 Warning