

## TURBOFAN E28-4

### 4 TRAY FULL SIZE ELECTRIC CONVECTION OVEN

With all the power and all the performance, the E28-4 provides it all. With twin bi-directional reversing fans, dual heating elements (5.6kW total) and four full size sheet pan capacity, this model offers the largest capacity of the 20 Series. As with the E27 models dual halogen lamps and a compact footprint are standard.

#### STANDARD FEATURES

- 4 full size sheet pan capacity
- 3<sup>1</sup>/<sub>8</sub>" / 80mm tray spacing
- Twin bi-directional reversing fans
- 5.6kW heating (220-240V) / 5.0kW heating (208V)
- Dual halogen oven lamps
- Twin dia. 7" / 180mm full stainless steel oven fans
- 4 oven wire racks supplied



W 31<sup>7</sup>/<sub>8</sub>" H 26" D 30"

#### E28M4 - MANUAL CONTROL

- Compact 31<sup>7</sup>/<sub>8</sub>" / 810mm width
- Mechanical thermostat  
150-500°F / 50-260°C
- 60 minute timer with time up alarm



W 31<sup>7</sup>/<sub>8</sub>" H 26" D 30"

#### E28D4 - DIGITAL CONTROL

- Compact 31<sup>7</sup>/<sub>8</sub>" / 810mm width
- Digital display Time and Temperature controls
- Large easy view 3<sup>4</sup>/<sub>4</sub>" / 20mm high displays
- Electronic thermostat control
- Electronic timer
- Manual mode and Program mode
- 20 programs with 3 stage cooking and stage end alarms
- Steam injection mode (5 levels) and manual injection

#### ACCESSORIES



SK2731U Oven Stand

Double stacking kit  
E28M4/2 DSK272831 - adjustable feet  
E28M4/2C DSK272831C - castor



SK2731U Oven Stand

Double stacking kit  
E28D4/2 DSK272831 - adjustable feet  
E28D4/2C DSK272831C - castor

PRODUCT  
COMPARISON  
CHART



SPECIFICATIONS		Turbofan E22M3				Turbofan E23M3			
		E22M3	E22M3/ SK23	E22M3/2	E22M3/2C	E23M3	E23M3/ SK23	E23M3/2	E23M3/2C
RACK/SHELF POSITIONS		3	3/6	3/3/3	3/3/3	3	3/6	3/3/3	3/3/3
Rack Spacings		2 5/8"	2 5/8"	2 5/8"	2 5/8"	3 1/2"	3 1/2"	3 1/2"	3 1/2"
TRAY/PAN CAPACITY									
13" x 18" Half Sheet Pan		3	3/6	3/3/3	3/3/3	3	3/6	3/3/3	3/3/3
18" x 26" Full Sheet Pan									
12" x 20" Hotel Pan									
ELECTRICAL RATING									
110-120V 1 Phase		1.5kW	1.5kW	1.5kW/1.5kW	1.5kW/1.5kW				
208V 1 Phase						2.7kW	2.7kW	2.7kW/2.7kW	2.7kW/2.7kW
220-240V 1 Phase						3.0kW	3.0kW	3.0kW/3.0kW	3.0kW/3.0kW
208V 3 Phase									
220-240V 3 Phase									
Cordset Fitted		5-15P	5-15P	5-15P/5-15P	5-15P/5-15P	6-15P	6-15P	6-15P/6-15P	6-15P/6-15P
GAS RATING									
EXTERNAL									
	Width (inches)	24	24	24	24	24	24	24	24
	Height (inches)	21 3/4	56 3/8	57 1/2	60 3/4	23 7/8	58 1/2	61 7/8	65 1/8
	Depth (inches)	23 7/8	23 7/8	25 3/8	25 3/8	25 1/4	25 1/4	25 1/4	25 1/4
	Width (mm)	610	610	610	610	610	610	610	610
	Height (mm)	552	1439	1461	1543	607	1487	1571	1653
	Depth (mm)	608	608	645	645	642	642	643	642
INTERNAL									
	Width (inches)	19 1/2	19 1/2	19 1/2	19 1/2	19 1/2	19 1/2	19 1/2	19 1/2
(Oven / Prover)									
	Height (inches)	10	10	10	10	12	12	12	12
	Depth (inches)	13 3/8	13 3/8	13 3/8	13 3/8	13 3/8	13 3/8	13 3/8	13 3/8
	Width (mm)	495	495	495	495	495	495	495	495
	Height (mm)	250	250	250	250	305	305	305	305
	Depth (mm)	340	340	340	340	340	340	340	340
STANDARD FEATURES									
Mechanical Controls		•	•	•	•	•	•	•	•
Digital Display Controls									
Touch Screen Controls									
Mechanical Thermostat		•	•	•	•	•	•	•	•
Electronic Thermostat									
Mechanical Timer 60min		•	•	•	•	•	•	•	•
Electronic Timer 180min									
Low Velocity Single Direction Fan		1	1	1/1	1/1				
Bi-directional Reversing Fan(s)						1	1	1/1	1/1
Two speed Bi-directional Reversing Fan(s)									
Water Injection									
Moisture Injection									
Steam Injection									
Core Temperature Probe Kit									
Broil Element / Mode									
Porcelain Enamel Oven Chamber		•	•	•	•	•	•	•	•
Halogen Oven Lights						1	1	1/1	1/1
Drop Down Door		•	•	•	•	•	•	•	•
Field Reversible Side Hinged Door									
Pendulum Operation Door Handle									
Safe-Touch Vented Door		•	•	•	•	•	•	•	•
Easy-Clean Oven Door Glass		•	•	•	•	•	•	•	•
Plug-In Door Seal		•	•	•	•	•	•	•	•
Oven Racks Supplied		3	3	6	6	3	3	6	6
Dual Proof and Holding Modes									
Autofill Water System									
Double Stacking Kit – Adjustable Feet				•				•	
Double Stacking Kit – Castor			Option		•		Option		•



d Tubofan E23D3				m Turbofan E27M2				m Turbofan E27M3			
E23D3	E23D3/ SK23	E23D3/2	E23D3/2C	E27M2	E27M2/ SK2731N	E27M2/2	E27M2/2C	E27M3	E27M3/ SK2731N	E27M3/2	E27M3/2C
3	3/6	3/3/3	3/3/3	2	2/6	2/2/3	2/2/3	3	3/6	3/3/3	3/3/3
3 1/2"	3 1/2"	3 1/2"	3 1/2"	4 1/2"	4 1/2"	4 1/2"	4 1/2"	3 1/2"	3 1/2"	3 1/2"	3 1/2"
3	3/6	3/3/3	3/3/3	4	4/12	4/4/6	4/4/6	6	6/12	6/6/6	6/6/6
				2	2/6	2/2/3	2/2/3	3	3/6	3/3/3	3/3/3

2.7kW	27kW	2.7kW/2.7kW	2.7kW/2.7kW	2.7kW	2.7kW	2.7kW/2.7kW	2.7kW/2.7kW	4.2kW	4.2kW	4.2kW/4.2kW	4.2kW/4.2kW
3.0kW	3.0kW	3.0kW/3.0kW	3.0kW/3.0kW	3.0kW	3.0kW	3.0kW/3.0kW	3.0kW/3.0kW	4.7kW	4.7kW	4.7kW/4.7kW	4.7kW/4.7kW
6-15P	6-15P	6-15P/6-15P	6-15P/6-15P	6-15P	6-15P	6-15P/6-15P	6-15P/6-15P	6-20P	6-20P	6-20P/6-20P	6-20P/6-20P
24	24	24	24	31 3/8	31 3/8	31 3/8	31 3/8	31 3/8	31 3/8	31 3/8	31 3/8
23 3/8	58 1/2	61 3/8	65 3/8	23 3/8	58 1/2	61 3/8	65 3/8	23 3/8	58 1/2	61 3/8	65 3/8
25 1/4	25 1/4	25 1/4	25 1/4	30	30	30	30	30	30	30	30
610	610	610	610	810	810	810	810	810	810	810	810
607	1487	1571	1653	607	1487	1571	1653	607	1487	1571	1653
642	642	643	642	762	762	762	762	762	762	762	762
19 1/2	19 1/2	19 1/2	19 1/2	27 3/8	27 3/8	27 3/8	27 3/8	27 3/8	27 3/8	27 3/8	27 3/8
12	12	12	12	12	12	12	12	12	12	12	12
13 3/8	13 3/8	13 3/8	13 3/8	18 1/2	18 1/2	18 1/2	18 1/2	18 1/2	18 1/2	18 1/2	18 1/2
495	495	495	495	695	695	695	695	695	695	695	695
305	305	305	305	305	305	305	305	305	305	305	305
340	340	340	340	470	470	470	470	470	470	470	470

				•	•	•	•	•	•	•	•
•	•	•	•								
				•	•	•	•	•	•	•	•
•	•	•	•								
•	•	•	•								
1	1	1/1	1/1	1	1	1/1	1/1	1	1	1/1	1/1
•	•	•	•								
•	•	•	•	•	•	•	•	•	•	•	•
1	1	1/1	1/1	2	2	2/2	2/2	2	2	2/2	2/2
•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•
3	3	6	6	2	2	4	4	3	3	6	6
		•				•				•	
	Option		•		Option		•		Option		•