

TURBOFAN P8

8 TRAY FULL SIZE ELECTRIC PROOFER/HOLDING CABINET

The P8M model is an 8 tray proofer/holding cabinet with style and durability. An auto-fill humidity generator and holding cabinet function mode are standard with easy to use controls. This unit can be stand-alone or stacked with the E32/G32 oven system and comes with a field reversible left or right hand hinged door. A plug-in connection makes it easy to install while a fully insulated double-skin cabinet construction ensures it's effectiveness.

STANDARD FEATURES

- 8 18" x 26" / 460 x 660 full size sheet pan capacity
- 16 18" x 13" / 460 x 330 half size sheet pan capacity
- 8 600 x 400 tray capacity
- 3" / 76mm tray spacing
- Compact 28 7/8" / 735mm width
- 110-120V plug-in
- 15A NEMA 5-15P cordset fitted
- Auto-fill water system standard



W 28 7/8" H 36" D 31 7/8"

P8M - MANUAL CONTROL

- Off/Proof/Hold mode selector switch.
- Mechanical thermostat 65-85°F
- Cabinet temperature thermometer

ACCESSORIES

- Optional 3M Cuno water filter kit complete with cartridge and connection fittings



Double stacking kit P8M/2 DSKP8 E32D5 on P8M G32D5 on P8M

TURBOFAN P12

12 TRAY FULL SIZE ELECTRIC PROOFER/HOLDING CABINET

This is a 12 tray proofer/holding cabinet made with the good looks and durability typical of this series. An auto-fill humidity generator and holding cabinet function mode are standard, with easy to use controls. This unit can be stand-alone or stacked with the E32 oven system, and comes with a field reversible left or right hand hinged door. The fully insulated double-skin cabinet construction ensures efficient heating and a plug-in connection makes it easy to install.

STANDARD FEATURES

- 12 18" x 26" / 460 x 660 full size sheet pan capacity
- 24 18" x 13" / 460 x 330 half size sheet pan capacity
- 12 600 x 400 tray capacity
- 2 7/8" / 74mm tray spacing
- Compact 28 7/8" / 735mm width
- 110-120V plug-in
- 20A NEMA 5-20P cordset fitted



W 28 7/8" H 44 1/2" D 31 7/8"

P12M - MANUAL CONTROL

- Off/Proof/Hold mode selector switch.
- Mechanical thermostat 65-85°F
- Cabinet temperature thermometer

ACCESSORIES

- Optional 3M Cuno water filter kit complete with cartridge and connection fittings



E32D5 on P12M