

GARLAND®

G-Series 48" Gas Restaurant Range With Flame Failure & Electronic Ignition

Project _____
Item _____
Quantity _____
CSI Section 11400
Approved _____
Date _____

Models

- GFE48-8LL
- GFE48-6G12LL
- GFE48-4G24LL
- GFE48-2G36LL



Model GFE48-8LL

Standard Features

- Flame failure protection: all burners
- Electric spark ignition on all burners, requiring single-phase 115V 60Hz or 240V 50Hz (specify)
- Large 27" (686mm) work top surface
- Stainless steel front and sides
- Stainless steel 5" (127mm) plate rail
- Stainless steel low-profile backguard
- 12" (305mm) section stamped drip trays w/ dimpled bottom
- 6" (152mm) adj. stainless steel legs
- Large, heavy-duty knobs
- Gas regulator
- Easy to access oven pilot
- Reinforced chassis

Standard on Applicable Models:

- Open storage in lieu of oven, (suffix S)
- Modular top (Suffix T) with stainless steel low profile backguard & 4" (102mm) adj. metal legs
- Ergonomic split cast-iron top ring grates
- 26,000 BTU/7.61 kW 2-piece cast-iron Starfire Pro® open top burner
- 5/8" (15mm) thick steel griddle plate w/ manual hi/lo valve control, 23" (584mm) working depth surface, standard on right, optional on left
- 4-1/4" (108mm) wide grease trough
- 18,000 BTU/5.27 kW cast-iron "H" style griddle burner per 12"(305mm) width of griddle
- 32,000 BTU/ 9.38 kW space-saver with

- cast-iron "H" style oven burner
- Snap-action modulating oven thermostat low to 500° F
- Nickel-plated oven rack and 3-position removable oven rack guide
- Large porcelain oven interior, fits standard sheet pans in both directions for standard ovens
- Square door design with strong, "keep-cool" oven door handle

Options & Accessories

- Manual hi/lo valve griddle control in lieu of thermostatic control
- Hot top 12" (305mm) plate in lieu of two open burners, manual valve controlled w/18,000 BTU/5.27 kW cast-iron "H" burner standard on left side
- Stainless steel backguard with removable high shelf
- Additional oven racks
- Four 6" (152mm) levelling swivel casters w/front locking
- Flanged deck mount legs
- Celsius temperature dials
- Piezo spark ignition for pilots on griddles

Specifications

Gas restaurant series range with 2 space-saver ovens, 20" (508mm) wide.

47-1/4" wide, 27" (686mm) deep work top surfaces.

Stainless steel front, sides and 5" wide front rail.

6" (152mm) legs with adjustable feet.

Total flame failure protection for all burners.

Electric spark ignition on all burners, requiring single-phase 115V 60Hz or 240V 50Hz (specify)

Eight Starfire Pro® 2-piece, 26,000 BTU/7.61 kW (natural gas), cast-iron open burners set in split cast-iron ergonomic grates.

Griddle or optional hot top with cast iron "H" style

burners, 18,000 BTU/5.27 kW (natural gas), in lieu of open burners.

Porcelain oven interior.

Heavy cast-iron "H" oven burner rated 32,000 BTU/ 9.38 kW (natural gas).

Oven controlled by even bake, fast recovery snap-action modulating oven thermostat.

NOTE: Use only Garland certified casters and approved restraining devices.



Garland Commercial Ranges Ltd.
1177 Kamato Road,
Mississauga, Ontario
L4W 1X4 CANADA

General Inquires 1-905-624-0260
USA Sales, Parts and Service 1-800-424-2411
Canadian Sales 1-888-442-7526
Canada or USA Parts/Service 1-800-427-6668

www.garland-group.com
8082A
04/25



G-Series 48" Gas Restaurant Range /
Flame Failure & Electronic Ignition

G-Series 48" Gas Restaurant Range /
Flame Failure & Electronic Ignition

Gas input ratings shown for installations up to 2000 ft., (610m) above sea level. Please specify altitudes over 2000 ft.

This product is not approved for residential use.

Note: Installation clearance reductions are applicable only where local codes permit.

Model Number	Description	Total BTU/Hr Natural Gas	Shipping Information		
			Lbs.	Kg	Cu. Ft.
GFE48-8LL	Eight Open Burners w/ Two Space-Saver Ovens	272,000	572	259	65
GFE48-6G12LL	12" Griddle, Six Open Burners w/ Two Space-Saver Ovens	238,000	602	273	65
GFE48-4G24LL	24" Griddle, Four Open Burners w/Two Space-Saver Ovens	204,000	667	303	65
GFE48-2G36LL	36" Griddle, Two Open Burners w/Two Space-Saver Ovens	170,000	672	305	65

Width In (mm)	Depth In (mm)	Height w/LPBG In (mm)	Oven Interior-in (mm)			Combustible Wall Clearance-In (mm)		Entry Clearances In (mm)		Manifold Operating Pressure	
			Height	Depth	Width	Sides	Rear	Crated	Uncrated	Natural	Propane
47-1/4 (1200)	34-1/2 (876)	45-3/8" (1153)	13 (330)	26 (660)	20 (508)	14 (356)	6 (152)	37 (940)	36-1/2 (927)	4.5" WC 11 mbar	10.0" WC 25 mbar

LPBG = Low Profile Backguard.

Burner Ratings (BTU/Hr/kW)			
Gas Type	Open Top	Griddle/Hot Top	Space-Saver Oven
Natural	33,000/9.67	18,000/5.27	32,000/9.38
Propane	26,000/7.61	18,000/5.27	28,000/8.20

Electrical Supply: GFE models with 115V 60 Hz 1-phase, 0.1 amps; 6 ft. (1.8m) power cord with NEMA 5-15P plug. Power cord not supplied with 240V 50 Hz 1-phase 0.05 amps models.

Garland reserves the right to make changes to the design or specifications without prior notice.

Garland Commercial Ranges Ltd.
1177 Kamato Road,
Mississauga, Ontario
L4W 1X4 CANADA

General Inquires 1-905-624-0260
USA Sales, Parts and Service 1-800-424-2411
Canadian Sales 1-888-442-7526
Canada or USA Parts/Service 1-800-427-6668

www.garland-group.com
8082A
04/25