

# U.S. Range

## U-Series 48" Gas Restaurant Range

Project \_\_\_\_\_  
 Item \_\_\_\_\_  
 Quantity \_\_\_\_\_  
 CSI Section 11400  
 Approved \_\_\_\_\_  
 Date \_\_\_\_\_

### Models

- U48-8RS      • U48-6G12RS      • U48-4G24RS      • U48-2G36RS      • U48-G48RS
- U48-8SS      • U48-6G12SS      • U48-4G24SS      • U48-2G36SS      • U48-G48SS
- U48-8LL      • U48-6G12LL      • U48-4G24LL      • U48-2G36LL      • U48-G48LL



Model U48-8LL

### Standard Features

- Large 27" (686mm) work top surface
- Stainless steel front and sides
- Stainless steel 5" (127mm) plate rail
- Stainless steel backguard, w/ removable stainless steel shelf
- 12" (305mm) section stamped drip trays w/ dimpled bottom
- 6" (152mm) adj. stainless steel legs
- Large, heavy-duty knobs
- Gas regulator
- Easy to access oven pilot light
- Reinforced chassis corners

#### Standard on Applicable Models:

- Open storage in lieu of oven, (suffix S)
- Modular top (Suffix T) with stainless steel low-profile backguard & 4" (102mm) adj. metal legs
- Ergonomic split cast-iron top ring grates
- Powerful 32,000 BTU/9.37 kW 2-piece cast-iron geometric open top burner
- 5/8" (15mm) thick steel griddle plate w/ manual hi/lo valve control, 23" (584mm) working depth surface, standard on right, optional on left
- 4-1/4" (108mm) wide grease trough
- 18,000 BTU/5.27 kW cast-iron "H" style griddle burner per 12" (305mm) width of griddle
- Front serviceable griddle plate
- 32,000 BTU/9.38 kW space-saver or 38,000 BTU/11.13 kW standard cast-iron "H" style oven burner
- Snap-action modulating oven

- thermostat low to 500° F
- Nickel-plated oven rack and 3-position removable oven rack guide
- Large oven w/ porcelain ribbed bottom & door, aluminized steel top, sides and back; standard oven fits standard sheet pans in both directions
- Square door design with strong, "keep-cool" oven door handle

### Options & Accessories

- Snap-action modulating griddle control 175° to 425° F
- Hot top 12" (305mm) plate in lieu of two open burners, manual valve controlled w/ 18,000 BTU/5.27 kW cast-iron "H" burner standard on left side
- Low-profile 9-3/8" (238mm) backguard stainless steel front and sides
- Additional oven racks
- Four 6" (152mm) levelling swivel casters w/ front locking
- Flanged deck mount legs
- Celsius temperature dials
- Piezo spark ignition for pilots on griddles

### Specifications

Gas restaurant series range with 2 space-saver ovens, 20" (508mm) wide or large capacity oven 26-1/4" (667mm) wide.

47-1/4" wide, 27" (686mm) deep work top surfaces.

Stainless steel front, sides and 5" wide front rail.

6" (152mm) legs with adjustable feet.

Eight powerful 2-piece 32,000 BTU/9.37 kW (Natural Gas), cast open burners set in split cast-iron ergonomic grates.

Griddle or optional hot top with cast-iron "H" style burners, 18,000 BTU/5.27 kW (natural gas), in lieu of open burners.

Front serviceable griddle plate.

Porcelain oven bottom and door liner and heavy-duty "keep-cool" door handle.

Heavy cast-iron "H" oven burner rated 32,000 BTU/ 9.38 kW (natural gas) for space-saver oven, and 38,000 BTU/11.13 kW (natural gas) for standard oven

Oven controlled by even bake, fast recovery snap-action modulating oven thermostat.

Available with storage base in lieu of oven(s).

NOTE: Use only Garland certified casters and approved restraining devices.



U-Series 48" Gas Restaurant Range

Garland Commercial Ranges Ltd.  
 1177 Kamato Road,  
 Mississauga, Ontario  
 L4W 1X4 CANADA

General Inquires 1-905-624-0260  
 USA Sales, Parts and Service 1-800-424-2411  
 Canadian Sales 1-888-442-7526  
 Canada or USA Parts/Service 1-800-427-6668

[www.garland-group.com](http://www.garland-group.com)  
 8094  
 09/24



# U.S. Range

## U-Series 48" Gas Restaurant Range

Gas input ratings shown for installations up to 2000 ft., (610m) above sea level. Please specify altitudes over 2000 ft.

This product is not approved for residential use.

Note: Installation clearance reductions are applicable only where local codes permit.

**TOP VIEW**  
 1-1/2" [39mm] (width)  
 34-1/2" [876mm] (depth)  
 27-1/4" [691mm] (width)  
 5" [127mm] (height)

**FRONT VIEW**  
 47-1/4" [1200mm] (width)  
 21" [533mm] (height)  
 57" [1447mm] (height)  
 23 1/4" [590mm] (height)  
 Ø 3/4" [19mm] REAR GAS INPUT  
 7-1/2" [191mm] / 6" [153mm] / OPTIONAL 5" [127mm] CASTERS

**RIGHT VIEW**  
 12-1/8" [307mm] (width)  
 18-5/16" [465mm] (height)  
 51" [1295mm] STD BACKGUARD W/ HIGH SHELF  
 39-3/8" [1000mm] LOW PROFILE BACKGUARD  
 13-7/8" [352mm] ADD WHEN DOOR OPEN

**OVEN DIMENSIONS**  
 15-1/4" [387mm] (width)  
 4-3/4" [120mm] (width)  
 21-13/16" [554mm] (width)

Model Number	Open Burners	Griddle	Oven(s)	Total BTU/Hr Natural	Ship Wt.	
					Lbs.	Kg
U48-8LL	8	—	(2) 20"	320,000	572	259
U48-8RS	8	—	(1) 26"	294,000	539	264
U48-8SS	8	—	—	256,000	402	182
U48-6G12LL	6	12"	(2) 20"	274,000	602	273
U48-6G12RS	6	12"	(1) 26"	248,000	569	258
U48-6G12SS	6	12"	—	210,000	432	196
U48-4G24LL	4	24"	(2) 20"	228,000	667	303
U48-4G24RS	4	24"	(1) 26"	202,000	604	274

Model Number	Open Burners	Griddle	Oven(s)	Total BTU/Hr Natural	Ship Wt.	
					Lbs.	Kg
U48-4G24SS	4	24"	—	164,000	497	255
U48-2G36LL	2	36"	(2) 20"	182,000	672	305
U48-2G36RS	2	36"	(1) 26"	156,000	639	290
U48-2G36SS	2	36"	—	118,000	502	228
U48-G48LL	—	48"	(2) 20"	136,000	692	314
U48-G48RS	—	48"	(1) 26"	110,000	659	299
U48-48GSS	—	48"	—	72,000	522	237

Shipping volume, all models= 65 Cu Ft

Width In (mm)	Depth <sup>2</sup> In (mm)	Height w/shelf In (mm)	Oven Interior-in (mm)			Combustible Wall Clearance-in (mm)		Entry Clearances In (mm)		Manifold Operating Pressure	
			Height	Depth	Width*	Sides	Rear	Crated	Uncrated	Natural	Propane
47-1/4 (1200)	34-1/2 (876)	57 (1448)	13 (330)	26 (660)	26-1/4 (667)	14 (356)	6 (152)	37 (940)	36-1/2 (927)	4.5" WC (11 mbar)	10" WC (25 mbar)

\*Space-saver oven is 20" (508mm) wide

Burner Ratings (BTU/Hr/kW)				
Gas Type	Open Top	Griddle/Hot Top	Standard Oven	Space-Saver Oven
Natural	32,000/9.37	18,000/5.27	38,000/11.13	32,000/9.37
Propane	26,000/7.61	18,000/5.27	32,000/9.38	28,000/8.20

Garland/US Range reserves the right to make changes to the design or specifications without prior notice.

Garland Commercial Ranges Ltd.  
 1177 Kamato Road,  
 Mississauga, Ontario  
 L4W 1X4 CANADA

General Inquires 1-905-624-0260  
 USA Sales, Parts and Service 1-800-424-2411  
 Canadian Sales 1-888-442-7526  
 Canada or USA Parts/Service 1-800-427-6668

www.garland-group.com  
 8094  
 09/24

