



CYCLONE SERIES FULL-SIZE ELECTRIC CONVECTION OVENS

SERIES: GDCO-E



Bakers Pride® GDCO-E series convection ovens feature both single and double-stacked models with electric operation. The synchronized doors are fully insulated and feature a cool-touch handle. The two-speed fan has a 900 rpm low-speed setting for precise cooking. This model is serviceable from the front and includes stainless steel front, top, sides, and doors. The lighted oven chamber features porcelain enamel interiors over heavy-gauge steel, eleven-position removable rack guides with 1.62" spacing, and five chrome plated racks. Standard rotary controls are simple to use and include a cool-down function and continuous-ring timer.



FEATURES AT A GLANCE

- Electric operation 10.5 kW per oven
- Electronic temperature control
- 150–550°F (65–287°C) temperature range
- 60/40 split synchronized doors with single handle
- Stainless steel front, top, sides, doors, and door seals
- Double-pane, thermal glass door windows
- Interior oven light
- 60-minute, continuous-ring timer
- Two-speed, 1/4 hp fan motor with cool-down mode and low-speed setting (900 rpm)
- Porcelain enamel oven interior
- Eleven-position removable rack guides with 1.62" spacing
- Five heavy-duty, chrome-plated wire racks with stop
- Black-powder-coated legs with adjustable bullet feet
- Five-year door warranty
- Front-mounted, hinged control panel for easy service access
- Units are hardwired; plug and cord not included
- Two-year limited warranty

OPTIONS & ACCESSORIES


- 30" (762 mm) stainless steel legs and shelf
- Stainless steel legs with casters and shelf
- Rack stand with rack guides
- Stainless steel perf back
- Direct vent flue
- Oven racks
- Stacking brackets
- Gas conversion kits
- Stacking kit with 6" (152 mm) legs
- Stacking kit with casters
- 25" (635 mm) legs with 3" (76 mm)
- 25" legs with casters
- Solid doors
- Steam injection



CYCLONE SERIES FULL-SIZE ELECTRIC CONVECTION OVENS

SERIES: GDCO-E

EQUIPMENT DIMENSIONS



MECHANICAL SPECIFICATIONS

Model #	Overall Dim (W x H x D)	Interior Dim (W x H x D)	Carton Dim (W x H x D)	Cubic Feet	Cubic Meter	Ship Wt.
GDCO-E1	38.12" x 58.25" x 41.93" (968 x 1480 x 1065)	29" x 20" x 22.25" (737 x 508 x 567)	43" x 34" x 48.25" (1092 x 864 x 1226)	45.93	1.29	514 (234kg)
GDCO-E2	38.12" x 62" x 41.93" (968 x 1575 x 1065)	29" x 20" x 22.25" (737 x 508 x 567)	Shipped in two boxes as above specifications			

*Height includes legs

POWER SUPPLY

Model #	Watts	Voltage	Phase	Amps			Fan 50HZ		Fan 60HZ	
				L1	L2	L3	RPM-low	RPM-high	RPM-low	RPM-high
BCO-E1	10.5	208	3	30	30	28	748	1425	850	1725
BCO-E1	10.5	220/240	3	26	26	24	748	1425	850	1725
BCO-E1	10.5	208	1	48	48		748	1425	850	1725
BCO-E1	10.5	220/240	1	44	44		748	1425	850	1725

REQUIRED CLEARANCES

	Vent Hood	Direct Venting
Left	1" (25 mm)	N/A
Right	1" (25 mm)	N/A
Back	3" (76 mm)	N/A

Bakers Pride reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.



Freight Class: 110
FOB: Allen, 75013

9.27.2019

