



□ □ □ □ □ □ □ □ □ □ □ □ □ □ □

¹double width rack²wide-opening rack; side-loaded trays

CONSTRUCTION...Heavy-duty, high tensile, all-welded extruded aluminum. Fully reinforced with horizontal stabilizing bars to prevent buckling. Entire base frame and bolster pads are completely welded to form solid one-piece unit.

CABINET MATERIAL...Type 6463-T5 alloy. Vertical and horizontal frame members are 1"x1" x .070 extruded aluminum tubing. Corner gussets constructed of 1-1/2" x 1-1/2" x 5/8" thick angle are welded to the inside angles (bottom side) where horizontal cross bracing meets vertical uprights.

ANGLE SLIDES... 1-1/2" x 1-7/8" wide angle type slide. Welded-in-place, both vertically and horizontally for support. Each slide is ribbed in order to minimize galling and flaking, as well as easy pan sliding.

CASTERS...Four 5" diameter heavy-duty polyurethane, plate mounted, non-marking casters. Caster plates welded to frame and bolted to caster plate. All swivel.

ACCESSORIES/OPTIONS...

- ☐ Caster locks (2)
☐ Corner bumpers (4)
☐ Pan stop
☐ Perimeter bumper
☐ Vertical bumpers
☐ Solid base

CARTER-HOFFMANN

11

FOOD SERVICE EQUIPMENT

FIXED ANGLE & OVAL TRAY RACKS

SPECIFICATIONS

CARTER-HOFFMANN
1551 McCormick Ave., Mundelein, IL 60060
(847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981
www.carter-hoffmann.com



O1600 Series UNIVERSAL OVAL TRAY RACKS for Most Standard Oval Trays

CARTER-HOFFMANN



FOOD SERVICE EQUIPMENT
FIXED ANGLE & OVAL TRAY RACKS

SPECIFICATIONS

Printed in U.S.A. J30 0609
Carter-Hoffmann is a trademark
of Carter-Hoffmann LLC



	Model Number	Tray	Tray Slide		Overall Dimensions						Caster		Shipping	
		Capacity	Spacing		Height		Depth		Width	Diameter	Weight			
		see sizes below	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kgs
☐	O1610	10	6	152	70	1778	30	762	26 ¹ / ₂	673	5	127	99	45
☐	O1620 ¹	20	6	152	71 ⁵ / ₈	1819	30	762	51 ³ / ₄	1314	5	127	182	83

¹double width rack

CONSTRUCTION... Heavy-duty, high tensile, all-welded extruded aluminum. Fully reinforced with horizontal stabilizing bars to prevent buckling. Entire base frame and bolster pads are completely welded to form solid one-piece unit.

CABINET MATERIAL... Constructed of 1-1/4" x 1-1/2" x .070 wall tubing. Angle slides are 2" x 6-3/4" x .125" wall. Four welds per angle slide.

ANGLE SLIDES... 1-1/2" x 1-7/8" wide angle type slide. Welded-in-place, both vertically and horizontally for support. Each slide is ribbed in order to minimize galling and flaking, as well as easy pan sliding. Accepts oval tray sizes 20-3/4" x 25-1/2", 22-3/4" x 27-5/8" and 23-1/2" x 29".

CASTERS... Four 5" diameter platform casters. All swivel.

ACCESSORIES/OPTIONS...

- ☐ 5" polyurethane swivel platform caster
- ☐ Corner bumpers (4)
- ☐ Caster locks (2) for 5" platform casters
- ☐ Perimeter bumper
- ☐ Pan stop
- ☐ Vertical bumpers

Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN
1551 McCormick Ave., Mundelein, IL 60060
(847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981
www.carter-hoffmann.com