

PAN RACKS

STANDARD FIXED ANGLE & WIDE OPENING

Features & Benefits

- Extra sturdy construction and heavy gauge aluminum for extended life under rugged conditions
- 5" casters, all swivel, for easy transport
- O8620D: Extra depth to accommodates 18"x14" half size trays with no overhang

Standard Fixed Angle Racks for 18"x26" Trays - End Loaded

Model Number	Tray Capacity 18" x 26"	Tray Slide Spacing in (mm)	Overall Dimensions			Caster Diameter in (mm)	Class 125 Shipping Weight lbs (kg)
Height	Depth in (mm)	Width					
O8609	9	5-1/16 (129)	55 (1397)	26-1/4 (667)	20-5/8 (524)	5 (127)	77 (35)
O8611	11	5-1/16 (129)	64-3/16 (1630)	26-1/4 (667)	20-5/8 (524)	5 (127)	80 (36)
O8612	12	5-1/16 (129)	69-5/16 (1761)	26-1/4 (667)	20-5/8 (524)	5 (127)	82 (37)
O8616	16	3 (76)	57-3/16 (1453)	26-1/4 (667)	20-5/8 (524)	5 (127)	85 (39)
O8618	18	3 (76)	64-3/16 (1630)	26-1/4 (667)	20-5/8 (524)	5 (127)	87 (40)
O8620	20	3 (76)	69-5/16 (1761)	26-1/4 (667)	20-5/8 (524)	5 (127)	90 (41)
O8620D	20	3 (76)	69-5/16 (1761)	28-1/4 (718)	20-5/8 (524)	5 (127)	92 (42)
O8622	22 (double width rack)	5-1/16 (129)	64-3/16 (1630)	26-1/4 (667)	40-1/8 (1019)	5 (127)	154 (70)
O8624	24 (double width rack)	5-1/16 (129)	69-5/16 (1761)	26-1/4 (667)	40-1/8 (1019)	5 (127)	157 (71)
O8636	36 (double width rack)	3 (76)	64-3/16 (1630)	26-1/4 (667)	40-1/8 (1019)	5 (127)	159 (72)
O8640	40 (double width rack)	3 (76)	69-5/16 (1761)	26-1/4 (667)	40-1/8 (1019)	5 (127)	165 (75)

Wide Opening Fixed Angle Racks for 18"x26" Trays - Side Loaded

Model Number	Tray Capacity 18" x 26"	Tray Slide Spacing in (mm)	Overall Dimensions			Caster Diameter in (mm)	Class 125 Shipping Weight lbs (kg)
Height	Depth in (mm)	Width					
O8609W	9	5-1/16 (129)	55 (1397)	18-5/8 (473)	28-5/8 (727)	5 (127)	77 (35)
O8611W	11	5-1/16 (129)	64-3/16 (1630)	18-5/8 (473)	28-5/8 (727)	5 (127)	80 (36)
O8612W	12	5-1/16 (129)	69-5/16 (1761)	18-5/8 (473)	28-5/8 (727)	5 (127)	82 (37)
O8616W	16	3 (76)	57-3/16 (1453)	18-5/8 (473)	28-5/8 (727)	5 (127)	85 (39)
O8618W	18	3 (76)	64-3/16 (1630)	18-5/8 (473)	28-5/8 (727)	5 (127)	87 (40)
O8620W	20	3 (76)	69-5/16 (1761)	18-5/8 (473)	28-5/8 (727)	5 (127)	90 (41)