



## **HEATED** TRANSPORT CARTS

PH Heated Transport  
Non-Insulated Aluminum  
ST Satellite Transport  
EnduraHeat® Transport  
PH Correctional Transport  
Gridless® Heated Transport

PAGE 72-75  
PAGE 76  
PAGE 77  
PAGE 78  
PAGE 79-80  
PAGE 70

# HEATED TRANSPORT CARTS

## FOR 12"x20" STEAM TABLE PANS

### Features & Benefits

- Models available with top or bottom mounted forced air heating
- Models with channel, angle or universal slides for a variety of pan sizes
- Under-counter, 1/2 height, 3/4 height and full height cabinets
- All heating systems feature convection air heating for fast heat-up and recovery as well as even heating
- All stainless steel, welded unibody construction for durable long life
- Non-marking floating style wrap-around bumper is standard (except PH125, PH128 & PH129). Absorbs shocks and minimizes damage to cart and facility walls.
- Offset wheel-ahead caster configuration for a smoother ride over uneven surfaces (except PH125, PH128 & PH129)
- Optional full perimeter wrap-around bumper (PH125, PH128 & PH129)



PH1250

### Heated Transport Carts with Channel Slides for 12"x20" Pans - Top-Mount Heat



PH129

Model Number	Pan Capacity* 12"x20"x2.5"	Inside Working Height in (mm)	Overall Dimensions			Caster Diameter in (mm)	Class 100 Shipping Wt. lbs (kg)
			Height	Depth	Width		
PH125 (under-counter)	5	20-1/2 (521)	28-1/2 (724)	25-1/8 (638)	17-7/8 (454)	3 (76)	110 (50)
PH128	8	23-5/8 (600)	37-3/4 (946)	25-1/8 (638)	17-7/8 (454)	4 (102)	128 (58)
PH129	9	26 (660)	40-1/2 (1029)	25-1/8 (638)	17-7/8 (454)	4 (102)	134 (61)

\*Spacing is fixed on 2-3/4" centers

### Heated Transport Carts with Channel Slides for 12"x20" Pans - Bottom-Mount Heat



PH1200

Model Number	Pan Capacity* 12" x 20"x2.5"	No. of Doors	Inside Working Height in (mm)	Overall Dimensions			Caster Diameter in (mm)	Class 100 Shipping Weight lbs (kg)
				Height	Depth	Width		
PH1200	16	1	46 (1168)	58 (1473)	28 (711)	24 (610)	5 (127)	280 (127)
PH1215	21	2	30 (762)	42 (1067)	28 (711)	46-3/4 (1187)	5 (127)	325 (147)
PH1225	33	2	46 (1168)	58 (1473)	28 (711)	46-3/4 (1187)	5 (127)	350 (159)
PH1250	50	3	46 (1168)	58 (1473)	28 (711)	65-1/4 (1658)	5 (127)	450 (204)

\*Channel slides with spacing fixed on 2-3/4" centers. Specify pan/tray size when ordering.

See page 75 for Options and Accessories

Electrical Information  
NEMA Plug Type

1000 watts  
120 volts  
8.3 Amps  
60 Hz  
Single Phase

PH125  
PH128  
PH129

Electrical Information  
NEMA Plug Type

1530 watts  
120 volts  
12.8 Amps  
60 Hz  
Single Phase

PH1200

Electrical Information  
NEMA Plug Type

1650 watts  
120 volts  
13.7 Amps  
60 Hz  
Single Phase

PH1215  
PH1225  
PH1250



NSF/ANSI 4

