



HALF SIZE HEAVY DUTY MANUAL



Model: XAF-113

Half Size, 3 Shelf, Manual Control, 120v (With Humidity)
Unit Dimensions (W" x H" x D"): 23 5/8 x 16 7/8 x 28 1/8
Cavity Size (W" x H" x D"): 19 1/2 x 10 x 15 1/2; 1.75 cft.
One fan. NEMA 5-15P plug
Volts: 120 Watts: 1450 Amps: 12
Shipping Weight (lbs.): 120*



NEMA
5-15P
Plug

Stands available: OST-34A-C, OST-34A-CS.
Heavy-Duty 2-Oven Stand also available: OV-HDS
Stackable with CXC651 Stacking Kit

Model	Color	Volts	Watts	Amps	Unit Dimensions	Unit Wt.	Ship Wt.	Ship Dimensions	Cube	UPC#
XAF-113	Stainless	120	1450	12	w:23 5/8", h:16 7/8", d:28 1/8"	74 lbs.	120* lbs.	w:42", h:21 7/8", d:48"*	24.36*	654796-52113-5



Model: XAF-133

Half Size, 4 Shelf, Manual Control, 220v (With Humidity)
Unit Dimensions (W" x H" x D"): 23 5/8 x 20 x 28 1/8
Cavity Size (W" x H" x D"): 19 1/2 x 13 x 15 1/2; 2.27 cft.
One fan. NEMA 6-20P plug
Volts: 208-240 Watts: 2700 Amps: 20
Shipping Weight (lbs.): 125*



NEMA
6-20P
Plug

Stands available: OST-34A-C, OST-34A-CS.
Heavy-Duty 2-Oven Stand also available: OV-HDS
Stackable with CXC651 Stacking Kit

Model	Color	Volts	Watts	Amps	Unit Dimensions	Unit Wt.	Ship Wt.	Ship Dimensions	Cube	UPC#
XAF-133	Stainless	208-240	2700	20	w:23 5/8", h:20", d:28 1/8"	80 lbs.	125* lbs.	w:42", h:25", d:48"*	29.17*	654796-52133-3

We recommend that the end user have a standard ice-machine filter when using a humidity hookup.
3" between shelves

"Cool-touch" double wall glass door

Oven cavity is wrapped in high "R" value insulation

60 minute timer or continuous on

Timer beeps at end of cycle

Heat settings from 175°-500° F

Heavy duty stainless steel construction

High temperature motor bearings

Heavy duty door & hinge construction

LED light in door

Dimensions are designed to accommodate modular stacking for customized configuration

2 year Limited Warranty (one year On-site service & parts, 2nd year parts only)**

90 day warranty on light bulbs & gasket (not service center items); 30 days on glass; one year on motor

Freight class 200 NOTE: This model must ship by truck, not UPS



www.cadco-ltd.com



860.738.2500



info@cadco-ltd.com