

UNDER COUNTER ROAST-N-HOLD™ CONVECTION OVENS

- Fully insulated gentle under counter convection ovens designed to fit conveniently under standard 36" counter tops.
- Standard with easy to read and operate LED digital display (DE). Optional Deluxe controls (DX) offer 18 programmable menus with probe cooking.
- Cabinets can be stacked for flexibility.
- Non-venting oven, permitted by most local codes.
- Ships freight class 100



(MODEL SHOWN WITH OPTIONAL WINDOWS.)

Model	CO151X185DE CO151X185DX	CO151XUA5DE CO151XUA5DX	CO151XWUA5DE CO151XWUA5DX	CO151XWUA5DXSTK
Get Spec Sheet, Operating manual, wiring diagram and more!				

Additional Specs:

Function	Convection Cooking & Holding	Convection Cooking & Holding	Convection Cooking & Holding	Convection Cooking & Holding
Construction	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Humidity	No	No	Yes	Yes
Capacity	(5) 18" x 26 (460 x 660 MM) pans	(5) sets of universal angles*	(5) sets of universal angles*	Two compartments (5) sets of universal angles*
Probe Cooking	Yes (-DX Model only) 6" Probe included	Yes (-DX Model only) 6" Probe included	Yes (-DX Model only) 6" Probe included	Yes (-DX Model only) 6" Probe included
Casters	2-1/2" (64 MM)	2-1/2" (64 MM)	2-1/2" (64 MM)	2-1/2" (64 MM)
Width	24-5/8" (625 MM)	28" (715 MM)	28-1/4" (725 MM)	28-1/4" (725 MM)
Depth	32-1/8" (815 MM)	32-1/8" (815 MM)	34" (865 MM)	34" (865 MM)
Height	31-7/8" (810 MM)	31-3/4" (810 MM)	32" (815 MM)	66" (1676 MM)
Shipping Weight	240 LBS (109 KG)	265 LBS (120 KG)	280 LBS (127 KG)	560 LBS (254 KG)
Standard Power Requirements	2000 Watts, 120 Volts, 1 Phase 5-20P 20 Amp Service	2000 Watts, 120 Volts, 1 Phase 5-20P 20 Amp Service	2000 Watts, 120 Volts, 1 Phase 5-20P 20 Amp Service	(Each Compartment) 4700 Watts, 208 or 240 Volts, 1 Phase 6-30P 30 Amp Service
Notes & Accessories	1. Pan spacing on 3" (76 MM) centers. 2. Supplied with (1) wire grid. Available power option: 4700W, 208V, 1 Ph, 30A 3" Probe available (DX Model)	1. Pan spacing adjustable on 1-1/2" (40 MM) centers. 2. Supplied with (2) wire grids. Available power option: 4700W, 208V, 1 Ph, 30A 3" Probe available (DX Model)	1. Pan spacing adjustable on 1-1/2" (40 MM) centers. 2. Supplied with (2) wire grids. Available power option: 4700W, 208V, 1 Ph, 30A 3" Probe available (DX Model)	1. Pan spacing adjustable on 1-1/2" (40 MM) centers. 2. Supplied with (4) wire grids. Available power option: 4700W, 240V, 1 Ph, 30A 4700W, 208V, 3 Ph, 20A 3" Probe available (DX Model)
Warranty Level	2-Year Parts, 1-Year Labor	2-Year Parts, 1-Year Labor	2-Year Parts, 1-Year Labor	2-Year Parts, 1-Year Labor

*Universal angles hold pan sizes 22" x 20" (560 x 510), Roast & Bake Pans, 10" x 20" (255 x 510) Roast & Bake Pans, 18" x 26" (460 x 660) Bun Pans, 14" x 18" (355 x 460) Service Trays, and 12" x 20" (305 x 510) Steam Table Pans.

Specify power option and Standard (DE) or Deluxe (DX) model when ordering. See page 58 for details.