

FULL-SIZE 18KW QUIK THERM™ ROLL-IN OVENS

- Fully insulated QuikTherm™ ovens designed for flavorful results by slow roasting.
- Standard with easy to read and operate LED digital display (DE). Optional Deluxe controls (DX) offer 18 programmable menus with probe cooking.
- Roll-in ovens designed to be used with RH Series roll-in hot cabinets for maximum efficiency.
- Non-venting oven, permitted by most local codes.
- Ships freight class 100



Model	RR1332DE RR1332DX	RR1332WDE RR1332WDX	RRUA16DE RRUA16DX	RRUA16WDE RRUA16WDX
Get Spec Sheet, Operating manual, wiring diagram and more!				

Additional Specs:

Function	Rethermalize Prepackaged Meals	Rethermalize Prepackaged Meals	Rethermalize Bulk Food	Rethermalize Bulk Food
Construction	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Humidity	No	Yes	No	Yes
Capacity	Roll-In Rack with Angle Ledge Pan Slides for (32) 13 x 26" (330 x 660 MM) Baskets	Roll-In Rack with Angle Ledge Pan Slides for (32) 13 x 26" (330 x 660 MM) Baskets	Roll-In Rack with Universal Angle Pan Slides for (16) 18" x 26" or (32) 12" x 20" pans	Roll-In Rack with Universal Angle Pan Slides for (16) 18" x 26" or (32) 12" x 20" pans
Probe Cooking	Yes (-DX Model only) 3" Probe included	Yes (-DX Model only) 3" Probe included	Yes (-DX Model only) 3" Probe included	Yes (-DX Model only) 3" Probe included
Legs	Adjustable 10" Leveling Legs	Adjustable 10" Leveling Legs	Adjustable 10" Leveling Legs	Adjustable 10" Leveling Legs
Width	39" (991 MM)	39" (991 MM)	38-7/8" (987 MM)	37-1/8" (886 MM)
Depth	33-7/8" (861 MM)	33-7/8" (861 MM)	37" (940 MM)	36" (914 MM)
Height	77-5/8" (1972 MM)	77-5/8" (1972 MM)	77-5/8" (1971 MM)	74-1/8" (1883 MM)
Shipping Weight	668 LBS (303 KG)	668 LBS (303 KG)	577 LBS (262 KG)	577 LBS (262 KG)
Power Requirements	12,000 Watts, 208 or 240 Volts, 3 Phase 15-50P 50 Amp Service	12,000 Watts, 208 or 240 Volts, 3 Phase 15-50P 50 Amp Service	12,000 Watts, 208 or 240 Volts, 3 Phase 15-50P 50 Amp Service	12,000 Watts, 208 or 240 Volts, 3 Phase 15-50P 50 Amp Service
Notes & Accessories	1. Pan spacing on 3" (80 MM) centers. 2. Baskets NOT included Available power options: 12 kW, 480V, 3 Ph, 30A. 8 kW, 208 or 240V, 1 Ph, 50 A. Wire Baskets Extra Roll-In Rack 6" Probe available (DX Model)	1. Pan spacing on 3" (80 MM) centers. 2. Baskets NOT included Available power options: 12 kW, 480V, 3 Ph, 30A. 8 kW, 208 or 240V, 1 Ph, 50 A. Wire Baskets Extra Roll-In Rack 6" Probe available (DX Model)	1. Pan spacing on 3" (80 MM) centers. Available power options: 12 kW, 480V, 3 Ph, 30A. 8 kW, 208 or 240V, 1 Ph, 50 A. Extra Roll-In Rack 6" Probe available (DX Model)	1. 13. Pan spacing on 3" (80 MM) centers. Available power options: 12 kW, 480 Volts, 3 Ph, 30A. 8 kW, 208 or 240V, 1 Ph, 50 A. Extra Roll-In Rack 6" Probe available (DX Model)
Warranty Level	2-Year Parts, 1-Year Labor	2-Year Parts, 1-Year Labor	2-Year Parts, 1-Year Labor	2-Year Parts, 1-Year Labor

*Universal angles hold pan sizes 22" x 20" (560 x 510), Roast & Bake Pans, 10" x 20" (255 x 510) Roast & Bake Pans, 18" x 26" (460 x 660) Bun Pans, 14" x 18" (355 x 460) Service Trays, and 12" x 20" (305 x 510) Steam Table Pans.

Specify power option and Standard (-DE) or Deluxe (-DX) model when ordering. See page 58 for details.